DIN 67510-1:2020-05 (E)

Phosphorescent pigments and products - Part 1: Measurement and marking at the producer

Contents

Page

Foreword ... 4

1 Scope ... 5

2 Normative references ... 5

3 Terms and definitions ... 5

4 Measurement ... 6
4.1 Measured objects ... 6
4.1.1 General ... 6
4.1.2 Phosphorescent pigments ... 6
4.1.3 Phosphorescent products ... 7
4.2 Requirements on the excitation apparatus ... 7
4.3 Excitation and measurement ... 8
4.3.1 Temperature ... 8
4.3.2 Illuminance measuring instrument ... 8
4.3.3 Procedure ... 8
4.4 Measurement of light decay ... 8
4.4.1 Luminance ... 8
4.4.2 Effect of stray light ... 10
4.4.3 Documentation of measured values ... 10
4.5 Determination of the decay time ... 10
4.6 Measurement record ... 10

5 Marking of phosphorescent properties ... 11

Annex A (informative) Mathematical method for the approximate determination of the decay time ... 12
A.1 Application ... 12
A.2 Procedure ... 12
A.3 Example of linear extrapolation ... 12
A.4 Example of parabolic extrapolation ... 14

Annex B (normative) Determination of the complete and relative saturating excitation ... 16
B.1 Complete saturating excitation ... 16
B.2 Relative saturating excitation ... 16

Annex C (normative) Classification by the manufacturer ... 17

Annex D (informative) Classification by the manufacturer for applications outside safety marking ... 18

Annex E (informative) Comparison of luminance under various excitation conditions ... 19

Bibliography ... 22

Figures

Figure A.1 — Linear fit ... 14

Figure A.2 — Parabolic fit ... 15

Tables

Table A.1 — Extract from the measurement record 13

Table A.2 — Calculation 13

Table A.3 — Extract from the measurement record 14

Table A.4 — Calculation 15

Table C.1 — Classification by the manufacturer 17

Table D.1 — Classification by the manufacturer for applications outside safety marking 18

Table E.1 — Influence of the excitation duration in min or h on the luminances at different colour temperatures in Kelvin (K) with different light sources at an illuminance of 25 lx 20

Table E.2 — Influence of the excitation duration in min or h on the luminances at different colour temperatures in Kelvin (K) with different light sources at an illuminance of 50 lx 21