

DIN 5034-6:2007-02 (E)

Daylight in interiors - Part 6: Simplified determination of suitable dimensions for rooflights

Contents		Page
Foreword		3
Introduction		4
1 Scope		4
2 Normative references		4
3 Symbols		5
4 Daylight factor		6
5 Simplified assumptions		7
5.1 Obstructions		7
5.2 Transmittance		7
5.3 Reduction factor for frames, sash bars, etc		7
5.4 Dirt		8
5.5 Reflectance of internal room surfaces		9
6 Calculation of auxiliary parameters		9
6.1 Effect of rooflight wells		9
6.2 Effect of the shape of rooflights		10
6.3 Effect of finite room dimensions		10
7 Calculation of the necessary rooflight rough opening area		12
Bibliography		13
Figures Figure 1 -- Schematic overview for the explanation of uniformities g_1 and g_2		6
Figure 2 -- Reduction factor k_e to account for the effects of the light well at different angles of inclination W and a reflectance of the well walls of $S = 0,55$ in relation to the well index w		8
Figure 3 -- Overview of the geometric parameters of a rooflight well		10
Figure 4 -- Corrections a and b to account for the finite room length a and width b in relation to angles α and β , which are given by the ratio of one-half the room length or width to the distance between the working plane and the ceiling		11
Figure 5 -- Example showing the dimensions necessary for determining corrections for finite room lengths and widths		11
Tables Table 1 -- Relation between reduction factor k_2 and dirt load on the glazing (guidance values) Table 2 -- Reduction factor k_4 to account for the shape of rooflights		10