

ISO/TS 6417:2025-06 (E)

Microfluidic pumps - Symbols and performance communication

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5	Standard Datasheets	2
5.1	Naming	2
5.2	Schematic/symbol	2
5.3	Technology characteristics	3
5.3.1	General	3
5.3.2	Actuation Type	3
5.3.3	Requirement of additional consumables	3
5.3.4	Wetted material	3
5.3.5	Reversible flow	3
5.3.6	Closed loop possibility	3
5.3.7	Operational lifetime	3
5.3.8	Reusable	3
5.4	General working conditions	4
5.4.1	Maximum pressure delivered	4
5.4.2	Ability to work in an incubator	4
5.4.3	Self-priming	4
5.4.4	Lifetime until out of accuracy	4
5.4.5	Self-heating	4
5.4.6	Sound level	4
5.4.7	Certifications	4
5.4.8	Back pressure	4
5.5	Electrical characteristics	4
5.5.1	Power supply	4
5.5.2	Electromagnetic compatibility	4
5.6	Mechanical characteristics	5
5.6.1	Internal volume	5
5.6.2	Dimension - Size	5
5.6.3	Weight	5
5.6.4	Working pressure	5
5.6.5	Integration level	5
5.6.6	Outlet/Inlet connector and accessories	5
5.7	Flow characteristics	5
5.7.1	General	5
5.7.2	Standard deviation (stability)	5
5.7.3	Response time	5
5.7.4	Open state fluidic resistance	6
5.7.5	Flow rate range	6
Annex A (informative)	Datasheet and symbols for pumps	7
Bibliography		14