

DIN EN 12164:2011-08 (E)

Copper and copper alloys - Rod for free machining purposes

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 7 |
| 4 | Designations | 8 |
| 4.1 | Material | 8 |
| 4.1.1 | General | 8 |
| 4.1.2 | Symbol | 8 |
| 4.1.3 | Number | 8 |
| 4.2 | Material condition | 8 |
| 4.3 | Product | 8 |
| 5 | Ordering information | 9 |
| 6 | Requirements | 10 |
| 6.1 | Composition | 10 |
| 6.2 | Mechanical properties | 10 |
| 6.3 | Resistance to dezincification | 10 |
| 6.4 | Residual stress level | 11 |
| 6.5 | Dimensions and tolerances | 11 |
| 6.5.1 | Diameter or width across-flats | 11 |
| 6.5.2 | Shape tolerances | 11 |
| 6.5.3 | Straightness | 11 |
| 6.5.4 | Length | 11 |
| 6.5.5 | Corner radii | 12 |
| 6.5.6 | Twist of polygonal rod | 12 |
| 6.5.7 | Shaped ends | 12 |
| 7 | Sampling | 14 |
| 7.1 | General | 14 |
| 7.2 | Analysis | 14 |
| 7.3 | Mechanical tests | 14 |
| 7.4 | Dezincification resistance and stress corrosion resistance tests | 14 |
| 8 | Test methods | 14 |
| 8.1 | Analysis | 14 |
| 8.2 | Tensile test | 15 |
| 8.2.1 | General | 15 |
| 8.2.2 | Location of test pieces | 15 |
| 8.2.3 | Shape and size of test pieces | 15 |
| 8.2.4 | Procedure for testing | 15 |
| 8.2.5 | Determination of results | 15 |
| 8.3 | Hardness test | 15 |
| 8.4 | Dezincification resistance test | 16 |
| 8.5 | Stress corrosion resistance test | 16 |
| 8.6 | Determination of the electrical conductivity | 16 |

| | | |
|--|---|----|
| 8.7 | Retests | 16 |
| 8.7.1 | Analysis, tensile test, hardness test and dezincification resistance test, determination of the electrical conductivity | 16 |
| 8.7.2 | Stress corrosion resistance test | 16 |
| 8.8 | Rounding of results | 17 |
| 9 | Declaration of conformity and inspection documentation | 17 |
| 9.1 | Declaration of conformity | 17 |
| 9.2 | Inspection documentation | 17 |
| 10 | Marking, packaging, labelling | 17 |
| Annex A (normative) Determination of mean depth of dezincification | | 33 |
| A.1 | Introduction | 33 |
| A.2 | Procedure | 33 |
| A.3 | Expression of results | 33 |
| Bibliography | | 35 |
| Figures Figure 1 -- Measurement of twist of polygonal rod | | 12 |
| Figure 2 -- Shaped ends of rod, Types | | 13 |
| Figure A.1 -- Example of contiguous fields | | 34 |
| Tables Table 1 -- Indicative shaped ends dimensions | | 13 |
| Table 2 -- Composition of low alloyed copper alloys | | 18 |
| Table 3 -- Composition of copper-nickel-zinc alloys | | 19 |
| Table 4 -- Composition of copper-tin alloys | | 19 |
| Table 5 -- Composition of copper-zinc alloys | | 20 |
| Table 6 -- Composition of copper-zinc-lead alloys | | 21 |
| Table 7 -- Composition of complex copper-zinc alloys | | 23 |
| Table 8 -- Mechanical properties of rod of low alloyed copper alloys | | 24 |
| Table 9 -- Mechanical properties of rod of copper-nickel-zinc alloys | | 25 |
| Table 10 -- Mechanical properties of rod of copper-tin alloys | | 26 |
| Table 11 -- Mechanical properties of rod of copper-zinc alloys | | 27 |
| Table 12 -- Mechanical properties of rod of copper-zinc-lead alloys | | 28 |
| Table 13 -- Mechanical properties of rod of complex copper-zinc alloys | | 29 |
| Table 14 -- Tolerances on diameter of round rod (including deviation from circular form) | | 30 |
| Table 15 -- Tolerances on width across-flats of regular polygonal rod | | 30 |
| Table 16 -- Tolerances on straightness of rod | | 31 |
| Table 17 -- Tolerances on length of nominal length rod | | 31 |
| Table 18 -- Corner radii for square, hexagonal and octagonal rod | | 31 |

Table 19 -- Maximum twist of square, hexagonal and octagonal rod32
Table 20 -- Sampling rate 32