DIN EN 1977:2013-04 (E)

Copper and copper alloys - Copper drawing stock (wire rod)

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Designations 5
4.1 Material 5
4.2 Product 6

5 Ordering information 7

6 Requirements 7
6.1 Composition 7
6.2 Elongation 7
6.3 Electrical properties 7
6.4 Annealability 12
6.5 Hydrogen embrittlement 12
6.6 Scale adhesion 13
6.7 Dimensions and tolerances 13
6.8 Surface condition 13
6.9 Joins 13

7 Sampling 13
7.1 General 13
7.2 Analysis (oxygen only) and measurement of diameter of Cu-ETP1 (CW003A) drawing stock 14
7.3 Annealability testing of Cu-ETP1 (CW003A) drawing stock 14
7.4 Analysis (other than oxygen) and measurement of elongation and electrical properties of Cu-ETP1 (CW003A) drawing stock 14
7.5 Tests on drawing stock in grades other than Cu-ETP1 (CW003A) 14

8 Test methods 15
8.1 Analysis 15
8.2 Elongation 15
8.3 Electrical resistivity 15
8.4 Annealability 16
8.5 Hydrogen embrittlement 16
8.6 Scale adhesion 16
8.7 Rounding of results 16

9 Declaration of conformity and inspection documentation 16
9.1 Declaration of conformity 16
9.2 Inspection documentation 17

10 Marking 17

Annex A (informative) Information on electrical resistivity and conductivity relationships 18

A.1 Volume resistivity 18
A.2 Standard annealed copper (IACS) 18
A.3 Commercial annealed copper 18
A.4 Nominal mass resistivity 18
A.5 Differences between measured and nominal values 19

Annex B (normative) Rapid Elongation Test method (AR-Test) for diameter 8 mm Cu-ETP1 wire rod 20

B.1 General 20
B.2 Procedure 20
B.3 Test results 22

Bibliography 23