

DIN EN 755-1:2016-10 (E)

Aluminium and aluminium alloys - Extruded rod/bar, tube and profiles - Part 1: Technical conditions for inspection and delivery

| Contents | | Page |
|---|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Ordering information | 6 |
| 5 | Requirements | 8 |
| 5.1 | Production and manufacturing processes | 8 |
| 5.2 | Quality control | 8 |
| 5.3 | Chemical composition limits | 8 |
| 5.4 | Mechanical properties | 8 |
| 5.5 | Freedom from surface defects | 9 |
| 5.6 | Tolerances on dimensions and form | 9 |
| 5.7 | Stress corrosion cracking resistance | 9 |
| 5.8 | Additional requirements | 9 |
| 6 | Test procedures | 9 |
| 6.1 | Sampling | 9 |
| 6.1.1 | Samples for chemical analysis | 9 |
| 6.1.2 | Specimens for mechanical testing | 10 |
| 6.1.3 | Test pieces for tensile test | 11 |
| 6.2 | Test methods | 11 |
| 6.2.1 | Chemical composition limits | 11 |
| 6.2.2 | Tensile testing | 11 |
| 6.2.3 | Brinell hardness testing | 11 |
| 6.2.4 | Measurement of dimensions | 11 |
| 6.2.5 | Surface finish | 12 |
| 6.2.6 | Resistance to stress corrosion cracking | 12 |
| 6.2.7 | Additional tests | 12 |
| 6.3 | Re-tests | 12 |
| 6.3.1 | Chemical composition limits | 12 |
| 6.3.2 | Mechanical properties | 12 |
| 6.3.3 | Other properties | 13 |
| 7 | Inspection documents | 13 |
| 8 | Marking of products | 13 |
| 9 | Packaging | 13 |
| 10 | Arbitration | 13 |
| Annex A (normative) Location of test pieces | | 14 |
| A.1 | Round, square and hexagonal bar | 14 |
| A.1.1 | For diameter (D) or width across flats (S) up to and including 40 mm | 14 |
| A.1.2 | For diameter (D) or width across flats (S) over 40 mm | 14 |

| | | |
|----------------------------|--|-----------|
| A.2 | Rectangular bar | 15 |
| A.2.1 | For thickness up to and including 12,5 mm | 15 |
| A.2.2 | For thickness (T) over 12,5 mm and up to and including 40 mm | 15 |
| A.2.3 | For thickness (T) exceeding 40 mm | 15 |
| A.3 | Tube | 16 |
| A.4 | Profiles | 16 |
| A.4.1 | For thickness up to and including 12,5 mm | 16 |
| A.4.2 | For thickness over 12,5 mm and up to and including 40 mm | 16 |
| A.4.3 | For thickness exceeding 40 mm | 17 |
| | | |
| Annex B (normative) | Resistance to stress-corrosion cracking for alloy EN AW-7075 in tempers | |
| | T73, T73510 and T73511 - Electrical conductivity | 18 |
| | | |
| Bibliography | | 19 |