

DIN EN ISO 7599:2018-05 (E)

Anodizing of aluminium and its alloys - Method for specifying decorative and protective anodic oxidation coatings on aluminium (ISO 7599:2018)

Contents		Page
European foreword	4
Foreword	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Information supplied by the customer to the anodizer	7
4.1 General	7
4.2 Essential information	7
4.3 Additional information	8
5 Tests	8
5.1 Sampling procedures	8
5.2 Test specimens	9
5.3 Acceptance tests	9
5.4 Referee tests	9
5.5 Production control tests	9
6 Coating thickness	9
6.1 General	9
6.2 Classification	9
6.3 Measurement of thickness	10
7 Quality of sealing	10
7.1 General	10
7.2 Assessment of quality of hydrothermal sealing	10
7.2.1 Referee test	10
7.2.2 Production control tests	11
7.3 Assessment of quality of cold sealing	11
7.4 Assessment of quality of other sealing treatments	11
8 Appearance and colour	11
8.1 Visible defects	11
8.2 Colour and surface texture	11
8.3 Production control	12
9 Corrosion resistance	12
10 Abrasion (wear) resistance	12
11 Resistance to cracking by deformation	13
12 Fastness to light and ultraviolet radiation	13
12.1 General	13
12.2 Fastness to light	13
12.3 Fastness to ultraviolet radiation	13
13 Light reflection properties	13
13.1 General	13
13.2 Total reflectance	14
13.3 Specular reflectance (high gloss)	14
13.4 Specular gloss (medium or low gloss)	15
13.5 Diffuse reflectance	15
13.6 Image clarity	15

14	Electrical breakdown potential	15
15	Continuity of coating	15
16	Mass per unit area (surface density) of coating	15
Annex A	(informative) Guide to grades of aluminium for anodizing	16
Annex B	(informative) Guidance on surface preparation	17
Annex C	(normative) Interpretation of average and local thickness requirements	19
Annex D	(informative) Calibration standards for eddy-current apparatus used to measure the thickness of anodic oxidation coatings on aluminium	20
Annex E	(informative) Guidance on cleaning materials for external architectural applications	24
Annex F	(informative) Summary of information to be supplied by the customer to the anodizer	25
Bibliography	26