

ISO 8251:2018 (E)

Anodizing of aluminium and its alloys — Measurement of abrasion resistance of anodic oxidation coatings

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Characteristics of abrasion tests
4.1	General
4.2	Abrasive-wheel-wear test
4.3	Abrasive jet test
4.4	Falling sand abrasion test
5	Abrasive-wheel-wear test
5.1	Principle
5.2	Apparatus
5.2.1	Abrasive-wheel-wear test apparatus
5.2.2	Abrasive strip
5.2.3	Eddy-current meter
5.2.4	Balance
5.3	Procedure
5.3.1	Standard specimen
5.3.2	Test specimen
5.3.2.1	Sampling
5.3.2.2	Size
5.3.2.3	Treatment before testing
5.3.3	Test procedure
5.4	Expression of results
5.4.1	General
5.4.2	Wear resistance
5.4.3	Mass wear resistance
5.4.4	Wear index
5.4.5	Mass wear index
6	Abrasive jet test
6.1	Principle
6.2	Apparatus
6.2.1	Abrasive jet test apparatus
6.2.2	Abrading medium
6.2.3	Eddy-current meter
6.2.4	Balance
6.3	Procedure
6.3.1	Standard specimen
6.3.2	Test specimen
6.3.2.1	Sampling
6.3.2.2	Size
6.3.2.3	Treatment before testing
6.3.3	Calibration of apparatus
6.3.4	Calibration of jet nozzle
6.3.4.1	General

- 6.3.4.2 Change of jet nozzle or abrasive characteristics with time
- 6.3.4.3 Jet nozzle replacement
- 6.3.5 Determination
- 6.3.6 Use of a reference specimen
- 6.4 Expression of results
 - 6.4.1 General
 - 6.4.2 Abrasive jet factor
 - 6.4.3 Mean specific abrasion resistance
 - 6.4.4 Relative mean specific abrasion resistance

7 Falling sand abrasion test

- 7.1 Principle
- 7.2 Apparatus
 - 7.2.1 Falling sand abrasion test apparatus
 - 7.2.2 Ohmmeter
 - 7.2.3 Abrading medium
- 7.3 Test specimen
 - 7.3.1 Sampling
 - 7.3.2 Size
 - 7.3.3 Treatment before testing
- 7.4 Test environment
- 7.5 Test conditions
- 7.6 Test procedure
 - 7.6.1 General
 - 7.6.2 Electrical conductivity method
 - 7.6.3 Spot diameter method
- 7.7 Expression of results
 - 7.7.1 Electrical conductivity method
 - 7.7.2 Spot diameter method

8 Test report

Annex A (normative) Preparation of the standard specimen

- A.1 General
- A.2 Aluminium standard specimen
 - A.2.1 Aluminium specification
 - A.2.2 Pretreatment
 - A.2.3 Anodizing
 - A.2.4 Sealing
- A.3 PMMA standard specimen

Annex B (informative) Other expressions of results for the abrasive-wheel-wear test

- B.1 Reference specimen
 - B.1.1 General
 - B.1.2 Initial determination
 - B.1.3 Test procedure
 - B.1.3.1 General
 - B.1.3.2 Comparative loss of thickness
 - B.1.3.3 Comparative loss of mass
 - B.1.4 Expression of results
 - B.1.4.1 Comparative wear rate
 - B.1.4.2 Comparative mass wear rate
- B.2 Standard specimen
 - B.2.1 General
 - B.2.2 Test procedure
 - B.2.3 Expression of results
 - B.2.3.1 Wear resistance coefficient
 - B.2.3.2 Mass wear resistance coefficient

Annex C (informative) Depth survey of abrasion resistance

- C.1 General
- C.2 Abrasive-wheel-wear test
 - C.2.1 Principle
 - C.2.2 Apparatus

- C.2.3 Procedure
- C.2.3.1 Determination
- C.2.4 Expression of results
- C.3 Abrasive jet test and falling sand abrasion test
- C.3.1 Principle
- C.3.2 Apparatus
- C.3.3 Procedure
- C.3.3.1 Test specimen
- C.3.3.2 Determination using the abrasive jet test
- C.3.3.3 Determination using the falling sand abrasion test
- C.3.4 Expression of results

Annex D (informative) Design of abrasive-wheel-wear test apparatus

Annex E (informative) Design of abrasive jet test apparatus

Annex F (informative) Design of falling sand abrasion test apparatus

Page count: 29