

ISO 23166:2018 (E)

Nickel alloys — Determination of tantalum — Inductively coupled plasma optical emission spectrometric method

Contents

| | |
|---------|---|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Reagents |
| 6 | Apparatus |
| 7 | Sampling and sample preparation |
| 8 | Procedure |
| 8.1 | Test portion |
| 8.2 | Preparation of test solution, TTA |
| 8.3 | Optimization of the spectrometer |
| 8.4 | Pre-determination of the test solution |
| 8.5 | Preparation of calibration solutions for bracketing, KI,Ta and Kh,Ta |
| 8.6 | Measurement of test solutions |
| 9 | Expression of results |
| 9.1 | Method of calculation |
| 9.2 | Precision |
| 9.2.1 | Laboratory tests |
| 9.2.2 | Wavelength for measurement |
| 9.2.3 | Statistical evaluation |
| 9.3 | Trueness |
| 10 | Test report |
| Annex A | (normative) Checking the performance of an inductively coupled plasma optical emission spectrometer |
| A.1 | General |
| A.2 | Resolution of a spectrometer |
| A.3 | Evaluating the short- and long-term stability |
| A.4 | Evaluating the background equivalent concentration |
| Annex B | (informative) Notes on the test programme |

Page count: 11