DIN EN 12168:2024-12 (E)

Copper and copper alloys - Hollow rod for free machining purposes

Contents

Page

European foreword 4

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Designations 9
4.1 Material 9
4.1.1 General 9
4.1.2 Symbol 9
4.1.3 Number 9
4.2 Material condition 9
4.3 Product 9

5 Ordering information 12

6 Requirements 14
6.1 Composition 14
6.2 Mechanical properties 14
6.3 Resistance to dezincification 14
6.4 Residual stress level 14
6.5 Dimensions and tolerances 14
6.5.1 Diameter or width across-flats 14
6.5.2 Tolerance on wall thickness 14
6.5.3 Eccentricity 15
6.5.4 Shape tolerances 15
6.5.5 Straightness 15
6.5.6 Length 15
6.5.7 Corner radii 15
6.5.8 Twist of polygonal hollow rod 16
6.6 Surface quality 16
6.7 Internal inclusion 17

7 Sampling 17
7.1 General 17
7.2 Analysis 17
7.3 Mechanical tests 17
7.4 Dezincification resistance and stress corrosion resistance tests 17

8 Test methods 18
8.1 Analysis 18
8.2 Tensile test 18
8.2.1 General 18
8.2.2 Location of test pieces 18
8.2.3 Shape and size of test pieces 18
8.2.4 Procedure for testing 18
8.2.5 Determination of results 18
8.3 Hardness test 18

8.4 Dezincification resistance test 19
8.5 Stress corrosion resistance test 19
8.6 Retests 19
8.6.1 Analysis, tensile, hardness and dezincification resistance tests 19
8.6.2 Stress corrosion resistance test 19
8.7 Rounding of results 19

9 Certificate of Compliance and inspection documentation 20
9.1 Certificate of Compliance 20
9.2 Inspection documentation 20

10 Marking, packaging, labelling 20

Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2014/68/EU (Pressure equipment Directive) aimed to be covered 39

Bibliography 40