

ISO 2107:2007-02 (E)

Aluminium and aluminium alloys - Wrought products - Temper designations

| Contents | | Page |
|------------------------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Terms and definitions | 1 |
| 3 | Basis of codification | 2 |
| 4 | Basic temper designations | 2 |
| 4.1 | F -- as fabricated | 2 |
| 4.2 | O -- annealed | 2 |
| 4.3 | H -- strain-hardened | 2 |
| 4.4 | W -- solution heat-treated | 2 |
| 4.5 | T -- thermally treated to produce stable tempers other than F, O or H | 3 |
| 5 | Subdivisions of O temper designations | 3 |
| 5.1 | O1 -- high-temperature annealed and slow cooled | 3 |
| 5.2 | O2 -- thermo-mechanically processed | 3 |
| 5.3 | O3 -- homogenized | 3 |
| 6 | Subdivisions of H temper designations | 3 |
| 6.1 | General | 3 |
| 6.2 | First digit after H | 3 |
| 6.3 | Second digit after H | 4 |
| 6.4 | Third digit after H | 5 |
| 6.5 | Other digits after H | 5 |
| 7 | Subdivisions of T temper designations | 5 |
| 7.1 | First digits (numerals 1 to 10) after T | 5 |
| 7.2 | Additional digits added to designations T1 to T10 | 7 |
| 7.3 | Assigned additional digits for stress-relieved T tempers | 7 |
| 7.4 | Assigned additional digits for stress-relieved W tempers | 8 |
| 7.5 | Assigned additional digits for variations of T7 type tempers | 8 |
| Annex A (informative) | Demonstration of response to heat treatment | 9 |