

DIN EN 13803-1:2011-03 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1435 mm and wider - Part 1: Plain line

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	8
5	Requirements	9
5.1	Background	9
5.1.1	General	9
5.1.2	Track alignment design parameters	9
5.1.3	Parameter quantification	10
5.2	Normal limits and exceptional limits for track alignment design parameters	10
5.2.1	Radius of horizontal curve R	10
5.2.2	Cant D	11
5.2.3	Cant deficiency I	11
5.2.4	Cant excess E	13
5.2.5	Cant gradient dD/ds	13
5.2.6	Rate of change of cant dD/dt	13
5.2.7	Rate of change of cant deficiency dI/dt	15
5.2.8	Length of transition curves in the horizontal plane LK	16
5.2.9	Length of circular curves and straights between two transition curves L_i	17
5.2.10	Vertical curves	18
5.2.11	Radius of vertical curve R_v	18
Annex A (informative)	Supplementary information for track alignment design related to shape and length of alignment elements	19
A.1	General	19
A.2	Summary of the properties of different transition curves	19
A.3	Further parameters that may be considered for track alignment curve design and a progressive system of design rules	21
A.3.1	Symbols and abbreviations	21
A.3.2	Objectives	23
A.3.3	Progressive track alignment design	23
A.3.4	Application	27
Annex B (informative)	Length of alignment elements (circular curves and straights) between two transition curves L_i	40
Annex C (informative)	Rules for converting parameter values for track gauges wider than 1435 mm	41
C.1	Scope	41
C.2	Symbols and abbreviations	41
C.3	Basic assumptions and equivalence rules	42
C.4	Detailed conversion rules	44
C.4.1	Radius of horizontal curve R_1 (5.2.1)	44

C.4.2	Cant D1 (5.2.2)	44
C.4.3	Cant deficiency I1 (5.2.3)	45
C.4.4	Cant excess E1 (5.2.4)	46
C.4.5	Cant gradient dD1/ds (5.2.5)	46
C.4.6	Rate of change of cant dD1/dt (5.2.6 of the main body of the standard)	47
C.4.7	Rate of change of cant deficiency dl1/dt (5.2.7)	48
C.4.8	Length of transition curves in the horizontal plane LK (5.2.8)	48
C.4.9	Other parameters (5.2.9, 5.2.10 and 5.2.11)	49

Annex D (normative) Track alignment design parameter limits for track gauges wider than 1435 mm 50

D.1	Scope	50
D.2	Requirements for a gauge of 1668 mm	50
D.2.1	General	50
D.2.2	Cant D1	50
D.2.3	Cant deficiency I1	50
D.2.4	Cant excess E1	51
D.2.5	Cant gradient dD1/ds	51
D.2.6	Rate of change of cant dD1/dt	51
D.2.7	Rate of change of cant deficiency dl1/dt	52
D.2.8	Length of circular curves and straights between two transition curves Li1	52
D.2.9	Vertical curves	53
D.2.10	Radius of vertical curve	53
D.3	Requirements for a gauge of 1524 mm	53
D.3.1	General	53
D.3.2	Cant D1	53
D.3.3	Cant deficiency I1	54
D.3.4	Cant excess E1	54
D.3.5	Cant gradient dD1/ds	55
D.3.6	Rate of change of cant dD1/dt	55
D.3.7	Rate of change of cant deficiency dl1/dt	55
D.3.8	Length of circular curves and straights between two transition curves Li1	56
D.3.9	Vertical curves	56
D.3.10	Radius of vertical curve	56

Annex E (informative) Track resistance to lateral forces generated by the rolling stock 57

E.1	Introduction	57
E.2	The effect of alignment design parameters on lateral forces generated by the rolling stock	57
E.2.1	Cant deficiency	57
E.2.2	Cant excess	58
E.2.3	The lateral strength limit of a track under loading (Prud'homme limit)	58
E.2.4	Factors influencing the resistance to track lateral displacement	58

Annex F (informative) Consequences on track resistance, stress and fatigue resulting from tilting body train systems 59

F.1	General	59
F.2	Basic principles applying to tilting body techniques	59
F.3	Safety requirements	59
F.3.1	Lateral axle force and track lateral resistance (track lateral shift)	59
F.3.2	Vehicle overturning	60
F.3.3	Comfort requirements	61

Annex G (informative) Constraints and risks associated with the use of exceptional limits 62

Annex H (informative) Recapitulation of the work carried out by the ORE B 55 Committee - Maximum permissible cant 63

H.1	Introduction	63
-----	--------------------	----

H.2	Criteria for safety against derailment at low speed through wheel-climbing	63
H.3	Limits for track twist	64
H.4	Rules applicable to the design of and checks performed on new vehicles with regard to their capability of coping with track twist values	65
H.5	List of reports published by the ORE B 55 Committee	65
Annex I (informative) A-deviation Switzerland		66
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC of the European Parliament and of the council of 17 June 2008 on the interoperability of the rail system within the Community		67
Bibliography		70