

# DIN EN 13262:2011-06 (E)

## Railway applications - Wheelsets and bogies - Wheels - Product requirements (includes Amendment A2:2011)

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Product definition .....</b>	<b>7</b>
<b>3.1</b>	<b>Chemical composition .....</b>	<b>7</b>
<b>3.1.1</b>	<b>Values to be achieved .....</b>	<b>7</b>
<b>3.1.2</b>	<b>Location of the sample .....</b>	<b>7</b>
<b>3.1.3</b>	<b>Chemical analysis .....</b>	<b>7</b>
<b>3.2</b>	<b>Mechanical characteristics .....</b>	<b>7</b>
<b>3.2.1</b>	<b>Tensile test characteristics .....</b>	<b>7</b>
<b>3.2.2</b>	<b>Hardness characteristics in the rim .....</b>	<b>9</b>
<b>3.2.3</b>	<b>Impact test characteristics .....</b>	<b>10</b>
<b>3.2.4</b>	<b>Fatigue characteristics .....</b>	<b>11</b>
<b>3.2.5</b>	<b>Toughness characteristic of the rim .....</b>	<b>12</b>
<b>3.3</b>	<b>Heat treatment homogeneity .....</b>	<b>13</b>
<b>3.3.1</b>	<b>Values to be achieved .....</b>	<b>13</b>
<b>3.3.2</b>	<b>Test pieces .....</b>	<b>13</b>
<b>3.3.3</b>	<b>Test method .....</b>	<b>13</b>
<b>3.4</b>	<b>Material cleanliness .....</b>	<b>13</b>
<b>3.4.1</b>	<b>Micrographic cleanliness .....</b>	<b>13</b>
<b>3.4.2</b>	<b>Internal integrity .....</b>	<b>14</b>
<b>3.5</b>	<b>Residual stresses .....</b>	<b>17</b>
<b>3.5.1</b>	<b>General .....</b>	<b>17</b>
<b>3.5.2</b>	<b>Values to be achieved .....</b>	<b>17</b>
<b>3.5.3</b>	<b>Test piece .....</b>	<b>18</b>
<b>3.5.4</b>	<b>Measurement methods .....</b>	<b>18</b>
<b>3.6</b>	<b>Surface characteristics .....</b>	<b>18</b>
<b>3.6.1</b>	<b>Surface appearance .....</b>	<b>18</b>
<b>3.6.2</b>	<b>Surface integrity .....</b>	<b>19</b>
<b>3.7</b>	<b>Geometric tolerances .....</b>	<b>19</b>
<b>3.8</b>	<b>Static imbalance .....</b>	<b>22</b>
<b>3.9</b>	<b>Protection against corrosion .....</b>	<b>22</b>
<b>3.10</b>	<b>Manufacturer's marking .....</b>	<b>23</b>
<b>Annex A (normative) Control of the hydrogen content in the steel for solid wheels at the melting stage .....</b>		<b>24</b>
<b>A.1</b>	<b>Sampling .....</b>	<b>24</b>
<b>A.2</b>	<b>Analysis methods .....</b>	<b>24</b>
<b>A.3</b>	<b>Precautions .....</b>	<b>24</b>
<b>Annex B (informative) Example of test method for the determination of fatigue characteristics .....</b>		<b>25</b>
<b>B.1</b>	<b>Test piece .....</b>	<b>25</b>
<b>B.2</b>	<b>Test rig .....</b>	<b>25</b>
<b>B.3</b>	<b>Test monitoring .....</b>	<b>25</b>
<b>B.4</b>	<b>Analysis of results .....</b>	<b>25</b>
<b>Annex C (informative) Strain gauge method for determining the variations of circumferential residual stresses located deep under the tread (Destructive method) .....</b>		<b>26</b>

C.1	Principle of the method .....	26
C.2	Procedure .....	26
C.3	Calculation of the variation of the circumferential residual stress located deep under the tread .....	27
<b>Annex D (informative) Ultrasonic method for determining the residual stresses in the rim (non-destructive method) .....</b>		<b>32</b>
D.1	Introduction .....	32
D.2	Method of measurement .....	32
D.3	Evaluation of results .....	33
<b>Annex E (informative) Product qualification .....</b>		<b>34</b>
E.1	General .....	34
E.2	Requirements .....	34
E.3	Qualification procedure .....	35
E.4	Qualification certificate .....	37
E.5	Qualification file .....	38
<b>Annex F (informative) Product delivery .....</b>		<b>39</b>
F.1	General .....	39
F.2	Delivery condition .....	40
F.3	Controls on each wheel .....	40
F.4	Batch control .....	40
F.5	Quality plan .....	43
F.6	Allowable rectification .....	43
<b>Annex ZA (informative) #Relationship between this European Standard and the essential requirements of Directive 2008/57/EC\$ .....</b>		<b>44</b>