DIN EN 13848-6:2014-07 (E)

Railway applications - Track - Track geometry quality - Part 6: Characterisation of track geometry quality

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 5
3.1 Terms and definitions 5
3.2 Symbols and abbreviations 5

4 Basic principles 6
4.1 Introduction 6
4.2 Transparency 6
4.3 Complexity 7
4.4 Track-vehicle interaction 7

5 Assessment of track geometry quality: state-of-the-art 7
5.1 General 7
5.2 Standard deviation (SD) 7
5.3 Isolated defects 8
5.4 Combination of various parameters 8
5.4.1 Combined standard deviation (CoSD) 8
5.4.2 Standard deviation of the combinations of parameters 9
5.4.3 Point mass acceleration method (PMA) 10
5.5 Methods based on vehicle response 10
5.5.1 Use of theoretical model 10
5.5.2 Use of direct measurement 11
5.6 Power Spectral Density (PSD) 11

6 Levels of aggregation and calculation methods 12

7 Classes of track geometry quality 12
7.1 General 12
7.2 Description of track quality classes (TQC) 13
7.3 Values of track quality classes 14
7.4 Assignment of TQCs 15
7.5 Possible application of TQCs 15

Annex A (informative) Point mass acceleration method (PMA) 17

A.1 Introduction 17
A.2 Description of the PMA model 17
A.3 Calculation of the PMA-assessment figure 17
A.4 Features of the PMA method 18

Annex B (informative) Vehicle Response Analysis methods (VRA) 19

B.1 Introduction 19
B.2 Determination of the assessment functions 19
B.3 Application of the assessment functions 21
B.4 Features of VRA methods 23

Annex C (normative) Method for calculating reference TQIs (TQIref) 24

C.1 Introduction 24
C.2 Description of the reference method 24

Annex D (informative) Method of classification of alternative TQI using the TQCs 26

D.1 Introduction 26
D.2 Description of the conversion method 26

Bibliography 28