

DIN EN 13848-6:2014-07 (E)

Railway applications - Track - Track geometry quality - Part 6: Characterisation of track geometry quality

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms, definitions, symbols and abbreviations	5
3.1	Terms and definitions	5
3.2	Symbols and abbreviations	5
4	Basic principles	6
4.1	Introduction	6
4.2	Transparency	6
4.3	Complexity	7
4.4	Track-vehicle interaction	7
5	Assessment of track geometry quality: state-of-the-art	7
5.1	General	7
5.2	Standard deviation (SD)	7
5.3	Isolated defects	8
5.4	Combination of various parameters	8
5.4.1	Combined standard deviation (CoSD)	8
5.4.2	Standard deviation of the combinations of parameters	9
5.4.3	Point mass acceleration method (PMA)	10
5.5	Methods based on vehicle response	10
5.5.1	Use of theoretical model	10
5.5.2	Use of direct measurement	11
5.6	Power Spectral Density (PSD)	11
6	Levels of aggregation and calculation methods	12
7	Classes of track geometry quality	12
7.1	General	12
7.2	Description of track quality classes (TQC)	13
7.3	Values of track quality classes	14
7.4	Assignment of TQCs	15
7.5	Possible application of TQCs	15
Annex A (informative)	Point mass acceleration method (PMA)	17
A.1	Introduction	17
A.2	Description of the PMA model	17
A.3	Calculation of the PMA-assessment figure	17
A.4	Features of the PMA method	18
Annex B (informative)	Vehicle Response Analysis methods (VRA)	19
B.1	Introduction	19
B.2	Determination of the assessment functions	19
B.3	Application of the assessment functions	21
B.4	Features of VRA methods	23

Annex C (normative) Method for calculating reference TQIs (TQIref)	24
C.1 Introduction	24
C.2 Description of the reference method	24
Annex D (informative) Method of classification of alternative TQI using the TQCs	26
D.1 Introduction	26
D.2 Description of the conversion method	26
Bibliography	28