

DIN EN 16272-6:2014-12 (E)

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 6: Intrinsic characteristics - In situ values of airborne sound insulation under direct sound field conditions

Contents		Page
Foreword		4
Introduction		5
1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Symbols and abbreviations	13
5	Sound insulation index measurements	15
5.1	General principle	15
5.2	Measured quantity	15
5.3	Test arrangement	16
5.4	Measuring equipment	20
5.4.1	Components of the measuring system	20
5.4.2	Sound source	21
5.4.3	Test signal	21
5.5	Data processing	21
5.5.1	Calibration	21
5.5.2	Sample rate	22
5.5.3	Background noise	22
5.5.4	Scanning technique using a single microphone	22
5.5.5	Scanning technique using nine microphones	23
5.5.6	Adrienne temporal window	23
5.5.7	Placement of the Adrienne temporal window	24
5.5.8	Low frequency limit and sample size	25
5.6	Positioning of the measuring equipment	26
5.6.1	Selection of the measurement positions	26
5.6.2	Post measurements	27
5.6.3	Additional measurements	27
5.6.4	Reflecting objects	27
5.6.5	Safety considerations	27
5.7	Sample surface and meteorological conditions	28
5.7.1	Condition of the sample surface	28
5.7.2	Wind	28
5.7.3	Air temperature	28
6	Measurement uncertainty	28
7	Measuring procedure	28
8	Test report	29
8.1	Expression of results	29
8.2	Further information	29

Annex A (informative) Measurement uncertainty	31
A.1 General	31
A.2 Expression for the calculation of sound insulation index	31
A.3 Contributions to measurement uncertainty	32
A.4 Expanded uncertainty of measurement	33
A.5 Measurement uncertainty based upon reproducibility data	33
Annex B (informative) Template of test report on airborne sound insulation of railway noise barriers	34
B.1 Template of test report	34
B.2 Test setup (example)	36
B.3 Test object and test situation (example)	38
B.4 Results (example)	40
Bibliography	46