

DIN EN 15273-2:2014-09 (E)

Railway applications - Gauges - Part 2: Rolling stock gauge

Contents		Page
Foreword		8
Introduction		15
1	Scope	16
2	Normative references	16
3	Terms and definitions	16
4	Symbols	17
5	Common requirements	24
5.1	Static and kinematic gauges	24
5.1.1	Description of the calculation method	24
5.1.2	Vehicle classes	24
5.1.3	Applicability of static and kinematic gauges depending on running gear of the vehicle ...	25
5.1.4	Limitations for the use of static gauges	26
5.1.5	Requirements for use of kinematic gauges	26
5.1.6	Dimensional tolerances on vehicles	27
5.2	Dynamic methods	27
5.2.1	General principles	27
5.2.2	Dynamic method based on a reference profile	27
Annexe A (normative) Gauge G1		29
A.1	General	29
A.1.1	Bogie classes	29
A.1.2	Rail-wheel adhesion coefficient	29
A.1.3	Minimum horizontal curve radius	29
A.2	Static gauge G1	30
A.2.1	Reference profiles for the lateral parts and upper parts	30
A.2.2	Reference profiles of the lower part of static gauge G1	31
A.2.3	Associated rules for static gauge G1	32
A.2.4	Reduction formulae	33
A.3	Kinematic gauge G1	34
A.3.1	General	34
A.3.2	Reference profiles of the upperparts of gauge G1	35
A.3.3	Reference profiles of the lower part of kinematic gauge G1	35
A.3.4	Determination of the vehicle heights	38
A.3.5	Contact ramps	51
A.3.6	Use of shunting devices on curved tracks	53
A.3.7	Conditions for embarkation onto ferries	54
A.3.8	Taking account of the transverse displacements of vehicles	55
A.3.9	Formulae	56
A.3.10	Reduction formulae applicable to wagons (dimensions in metres)	63
A.3.11	Formulae to be applied for bogies and associated parts	64
A.3.12	Verification of gauge of pantographs and non-insulated live parts on vehicle roof	65
A.3.13	Pantograph gauge verification for tilting body vehicles or running with $IP > IC$	70
A.3.14	Specific rules for doors in the open position and movable steps in the exit position	74
A.3.15	Position of steps	74
A.3.16	Tilting vehicles	75

A.4	Track operation position of the vehicles: angular displacement coefficient (A)	84
Annexe B (normative) Gauges GA, GB, GC		89
B.1	Common elements with gauge G1	89
B.2	Static gauges GA, GB, and GC (loading gauges)	89
B.2.1	Upper part reference profiles	90
B.2.2	Reduction calculation formulae for static gauges GA and GB	90
B.2.3	Reduction calculation formulae for static gauges GC	91
B.3	Kinematic gauges GA, GB, and GC	91
B.3.1	Upper part reference profiles	92
B.3.2	Reference profiles for lower parts	92
B.3.3	Formulae for traction units (except motor coaches)	92
B.3.4	Formulae for motor coaches	95
B.3.5	Formulae for coaches and vans	97
B.3.6	Formulae for wagons	99
Annexe C (normative) Gauges GB1, GB2		102
C.1	Static gauges GB1 and GB2	102
C.1.1	Reference profile of static gauge GB1	102
C.1.2	Kinematic gauges GB1 and GB2	104
Annexe D (normative) Kinematic gauge GI3		106
D.1	Reference profile GI3	106
D.2	Associated rules for the kinematic reference profile to determine the maximum vehicle profile	107
D.2.1	Traction units (except motor coaches)	107
D.2.2	Motor coaches	109
D.2.3	Coaches and vans	110
D.2.4	Wagons	112
Annexe E (normative) Gauge G2		115
E.1	Static gauge G2	115
E.1.1	Reference profile for static gauge G2	115
E.1.2	Reference profile of kinematic gauge G2	116
Annexe F (normative) Finnish gauge FIN1		117
F.1	General	117
F.2	Associated rules	117
F.2.1	Vertical position of the vehicle	117
F.2.2	Lower parts of the rolling stock	117
F.2.3	Rolling stock parts close to the wheel flanges	117
F.2.4	Rolling stock width	118
F.2.5	Movable steps and access doors opening outwards for coaches and motor coaches	118
F.2.6	Pantographs and non-insulated roof-mounted parts	118
F.2.7	Rules and instructions	118
F.3	Reduction formulae	118
F.3.1	General rules	118
F.3.2	Reduction formulae	119
F.4	Reference profiles of gauge FIN1	120
F.5	Increase in the minimum height of the lower part of the rolling stock able to pass over marshalling humps and rail brakes	121
F.6	Increase in the minimum height of the lower part of the rolling stock unable to pass over marshalling humps and rail brakes	121
F.7	Passage over transitions and humps	122
F.7.1	Position of rail brakes and other shunting devices	122
F.7.2	Running over marshalling hump passing track	123
F.8	Gauge of the vehicle lower step	123

F.8.1	General	123
F.8.2	Requirements for the distance between the step and the platform in the transverse plane	124
F.8.3	Gauge check	124
F.9	Gauge of outwards opening doors and of folded down steps for coaches and motor coaches	124
F.9.1	General	124
F.9.2	Requirements for the distance between the door and the fixed equipment in the transverse plane	125
F.9.3	Gauge check	125
F.10	Pantographs and non-insulated parts	126
Annexe G (normative) French gauge FR 3.3		127
G.1	General	127
G.2	Reference profile of kinematic gauge FR 3.3	128
G.3	Reference kinematic profiles for lower parts	128
G.4	Associated rules for kinematic gauge FR 3.3 for determining the kinematic gauge	128
G.4.1	Vertical reductions	128
G.4.2	Transversal reductions for heights $h > 3,250$ m	129
G.4.3	Verification of gauge of pantographs and non-insulated live parts on vehicle roof	134
Annexe H (normative) Belgian gauges BE1, BE2 and BE3		135
H.1	General	135
H.2	Associated rules	135
H.2.1	Rules for the lower parts	135
H.2.2	Upwards vertical displacements	135
H.2.3	Side doors in the open position	136
H.2.4	Movable step rules	136
H.2.5	Pantograph rules	136
H.3	Kinematic reference profiles for the upper parts	137
H.4	Reduction formulae	139
H.4.1	Reduction formulae for traction units	139
H.4.2	Reduction formulae for hauled vehicles	142
H.5	Kinematic gauge of the 3 kV and 25 kV pantograph in the collection position on the Belgian network	145
H.5.1	General principles	145
H.5.2	Verification of pantographs located between the end wheelsets or between the bogie centres (verification of stationary vehicle on a canted track)	145
H.5.3	Verification of pantographs located beyond the end wheelsets or beyond the bogie centres (verification in operation on an insufficiently canted track)	146
H.5.4	Pantographs in the lowered position	146
H.5.5	Other non-insulated roof-mounted parts	146
Annexe I (normative) Portuguese gauges PTb, PTb+, PTc		148
I.1	General	148
I.2	Kinematic reference profiles	149
I.3	Reference profiles for the lower part	152
I.4	Associated rules for PT gauges	153
I.4.1	Vertical displacements	153
I.4.2	Transverse displacements	153
I.4.3	Associated rules for the parts of height $h < 400$ mm above the running surface	153
I.4.4	Reduction formulae	154
I.5	Associated rules for pantographs and other roof-mounted parts	158
I.5.1	Reference profile for pantographs	158
I.5.2	Pantograph in collecting position	159
I.5.3	Pantograph in the lowered position and other roof-mounted parts	160
I.6	Associated rules for tilting body vehicles	160
I.6.1	Quasi-static displacements (z_p)	160
I.6.2	Calculation of the reductions	161

I.6.3	Requirement for adjusting the tilting system for vehicles fitted with active systems	162
I.6.4	Limits related to the speed of tilting body vehicles	163
Annexe J (normative) Swedish gauges SEa and SEc		164
J.1	Swedish dynamic gauges SEa and SEc: General	164
J.2	Reference profiles	165
J.3	Reference profile of gauge SEa	165
J.4	Reference profile for lower part of gauges SEa and SEc	166
J.5	Pantograph reference profile for gauge SEa	166
J.6	Dynamic reference profile SEc	167
J.6.1	Reference profile for parts below 0,15 m of gauge SEc	167
J.6.2	Reference profile for pantograph for gauge SEc	168
J.7	Methodology for calculating movements by means of geometric formulae	168
J.7.1	Curves in the horizontal plane	169
J.7.2	Straight track	171
J.7.3	Vertical curves, calculation of upper parts	172
J.7.4	Calculation of the lower parts	173
J.7.5	Marshalling humps	174
J.7.6	Ferry ramps	174
J.7.7	Pantograph	175
J.7.8	Swept envelope	175
J.8	Methodology for calculating movements by simulation	176
J.8.1	Modelling and simulations	178
J.8.2	Parameters to be considered in the simulations	178
J.8.3	Cases of simulation	179
J.8.4	Horizontal curves	179
J.8.5	Straight track	179
J.8.6	Running over points	180
J.8.7	Track parameters	180
J.8.8	Calculation parameters	180
J.8.9	Statistical post-processing	181
J.8.10	Geometric overthrow in a horizontal curve	181
J.8.11	Vertical geometric movement towards the upper part of the profile	182
J.8.12	Vertical geometric movement towards the lower part of the profile	182
J.8.13	Marshalling humps	183
J.8.14	Ferry ramps	184
J.8.15	Pantographs	184
J.8.16	Swept envelope	185
J.9	Checking relative to the permitted reference profile	185
J.10	Dynamic gauging method: verification	185
J.10.1	Verification by simulation	186
J.10.2	Verification by static testing	186
J.10.3	Verification by on-line running tests	187
J.10.4	(Informative) Dynamic gauge: Irregularities	187
J.11	(Informative) Two-dimensional statistical post processing	188
J.12	(Informative) Input data catalogue	189
Annexe K (normative) Static gauges OSJD		191
K.1	Static reference profiles of the upper parts (for rolling stock)	191
K.2	Associated rules	193
K.2.1	Additional overthrows for h 3,220 m	193
K.2.2	Reduction formulae	193
K.3	Determination of the allowable vertical dimensions	195
K.4	Static reference profiles for the lower parts	196
Annexe L (normative) German gauges DE1, DE2, DE3		198
L.1	Gauge DE1	198
L.1.1	Kinematic reference profile	198
L.1.2	Associated rules	199

L.2	Kinematic gauge DE2	200
L.2.1	Kinematic reference profile	200
L.2.2	Associated rules	201
L.3	Kinematic gauge DE3	202
L.3.1	Kinematic reference profile	202
L.3.2	Associated rules	202
L.4	Absolute gauging of pantographs	203
L.4.1	General	203
L.4.2	Associated rules	203
L.4.3	Contact wire	205
L.4.4	Responsibility for input data	205
Annexe M (normative) Netherlands gauges NL1 and NL2		208
M.1	Reference profiles of kinematic gauges NL1 and NL2	208
M.2	Associated rules	209
Annexe N (informative) UK gauging methods		210
N.1	General	210
N.1.1	Gauge types	210
N.1.2	Maintenance	210
N.1.3	Tolerances	210
N.1.4	Multiple operation	210
N.1.5	Configuration	210
N.1.6	Reference axes	211
N.1.7	Vehicle data	211
N.2	Static gauging	211
N.2.1	Principles	211
N.2.2	Vehicle geometry	212
N.2.3	Suspension displacements	213
N.3	Dynamic gauging	214
N.3.1	Principles	214
N.3.2	Geometric gauging	214
N.3.3	Absolute gauging	216
N.3.4	Comparative gauging	218
N.3.5	Vehicle shape and size	221
N.3.6	Range of operating conditions	222
N.3.7	Suspension movements	225
N.3.8	Calculating swept envelopes	225
N.3.9	Dynamic reference profiles	232
N.3.10	Assessing the vehicle	235
N.4	UK geometric gauges	236
Annexe O (informative) Recommended practice for dynamic gauging		237
O.1	Vehicle models	237
O.1.1	Principles	237
O.1.2	Vehicle conditions	237
O.1.3	Masses	237
O.1.4	Suspension modelling	238
O.1.5	Stiffness	238
O.1.6	Dampers	238
O.1.7	Air springs	238
O.1.8	Swing links	239
O.1.9	Friction	239
O.1.10	Active devices	239
O.1.11	Inter-vehicle connections	239
O.1.12	Suspension component tolerances	240
O.1.13	Suspension maintenance allowances	240
O.1.14	Suspension failure modes	240
O.1.15	Vehicle modelling accuracy	240

O.2	Validation of vehicle modelling	240
O.2.1	General notes on validation tests	240
O.2.2	Simulation model	242
O.2.3	Matching accuracy	243
O.2.4	Weighbridge test	243
O.2.5	Bogie rotation test	244
O.2.6	Sway test	244
O.2.7	Dynamic ride test	245
O.3	Simulation method	246
O.3.1	Principles	246
O.3.2	Dynamic analysis	246
O.3.3	Track data	247
O.3.4	Cant, speed and curve radius: general cases	247
O.3.5	Cant, speed and curve radius: specific cases	248
O.3.6	Application of cant and curve radius	248
O.3.7	Side wind loads	248
O.3.8	Transient outputs	248
O.3.9	Curving analysis	251
O.4	Example of a virtual route	252
O.5	Example of a drawing showing vehicle size and shape	255
O.6	Presentation of swept envelope data	256
O.6.1	Presentation of results	256
O.6.2	Heading format	256
O.6.3	Transient results matrix	257
O.6.4	Curving results matrix	258
Annexe P (normative) Spanish gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10		259
P.1	General	259
P.2	Static gauges GHE16, GEA16, GEB16, GEC16, GEE10 and GED10	260
P.2.1	Reference profiles for static gauges	260
P.2.2	Associated rules	268
P.3	Kinematic gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10	271
P.3.1	Reference profiles for kinematic gauges	271
P.3.2	Associated rules	280
Annexe Q (normative) Vehicle widening depending on the available spaces of the infrastructure ..		298
Annexe R (normative) Static and kinematic gauges: list of documents for a vehicle gauge conformance certification		299
R.1	General	299
R.2	List of documents to be produced for design control	299
R.3	List of documents to be taken into account to verify conformity to the gauge	299
Annexe S (informative) A-deviations		301
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC		303
Bibliography		309