

DIN EN 15313:2016-09 (E)

Railway applications - In-service wheelset operation requirements - In-service and off-vehicle wheelset maintenance

Contents		Page
European foreword		6
Introduction		7
1	Scope	8
2	Normative references	9
3	Terms and definitions	9
4	Maintenance	10
4.1	General	10
4.2	Maintenance organization	11
4.2.1	Maintenance organization plan	11
4.2.2	Maintenance plan	11
4.2.3	Service experience	12
4.2.4	Traceability - storage - transportation	12
4.3	Equipment and systems	14
4.4	Staff certification and competence	14
4.5	Qualification of an undertaking for the maintenance of in-service or off-vehicle wheelsets	14
5	Definition and illustrations of a boxed wheelset, its associated components and defects ..	16
5.1	Definition and illustrations of a wheelset	16
5.1.1	Wheelset	16
5.1.2	Axle	18
5.1.3	Wheel	19
5.1.4	Axle box	21
5.2	Functional references of the rail-wheel interface	21
5.2.1	Wheelset functional references	21
5.2.2	Wheel functional references	22
5.3	Definition and illustrations of defects	23
6	Requirements and operations	23
6.1	General	23
6.2	Requirements	24
6.2.1	In-service limit dimensions and positions	24
6.2.2	Special maintenance action for freight wagon axles according to axle load	27
6.2.3	Maintenance decision criteria for in-service wheels for all types of wheel	28
6.2.4	Maintenance decision criteria for in-service wheels for specific wheel types	31
6.2.5	Damage acceptance limits for axle bodies	31
6.2.6	Criteria for axle box (Annex C.5)	32
6.2.7	Criteria on boxed wheelsets	32
6.2.8	Specific requirements for tyred wheels and resilient wheels	33
6.2.9	Limit value for axle wheel seat diameter	34
6.3	Reprofiling operation	34
6.4	Dimensions and conditions after reprofiling or an operation on the rim	35
6.4.1	Front-to-front dimension "a2"	35
6.4.2	Diameter difference between wheels on the same axle	35
6.4.3	Limit values of radial run-out as a function of the maximum operating speed authorized for the vehicle	35

6.4.4	Wheel axial run-out as a function of the maximum operating speed authorized for the vehicle	35
6.4.5	Parts of the tread that are not re-profiled	35
6.4.6	Radial traces and radial defects on the internal side of the rim	36
6.5	Operations, examinations and inspections	36
6.5.1	General	36
6.5.2	Detection of tread defects	36
6.5.3	Detection of thermal damage on the wheel rim or tyre	37
6.5.4	Detection of wheel tread roll-over	37
6.5.5	Detection of damage to chamfered corner and flange	37
6.5.6	Detection of damage resulting from identification markings	37
6.5.7	Detection of defects on the external and internal face of the rim	37
6.5.8	Verification of web integrity	37
6.5.9	Verification of hub integrity	38
6.5.10	Verification of rim integrity - Detection of deep sub-surface tread defects	38
6.5.11	Detection of thermal defects on the web of a wheel used as a braking surface	38
6.5.12	Detection of overheating affecting the wheel rim-web transition on monobloc wheels	38
6.5.13	Verification of axle surface integrity	38
6.5.14	Detection of damage caused by corrosion	40
6.5.15	Detection of circumferential defects around the whole circumference	40
6.5.16	Detection of circumferential defects in a singular section of the circumference	40
6.5.17	Detection of notches and impact damage	41
6.5.18	Detection of longitudinal defects on axles	41
6.5.19	Detection of damage in interference fit zones	41
6.5.20	Verification after rectification	41
6.5.21	Verification of residual magnetism	41
6.5.22	Lubrication operation	41
6.5.23	Checking for axle box defects	41
6.5.24	Verification of wheelset electrical resistance after heavy maintenance of boxed wheelsets	41
6.6	Requirements for additional maintenance equipment and operations	42
7	In-service boxed wheelset maintenance	42
7.1	Maintenance plan	42
7.2	Wheelset protection during vehicle and bogie cleaning	42
8	Off-vehicle wheelset maintenance	42
8.1	Maintenance plan	42
8.2	Key operations for off-vehicle wheelset maintenance	43
8.3	Off-vehicle boxed wheelset cleaning	43
8.4	NDT Interval	43
9	Action to be taken on any wheelset after an incident in service or when not covered by the maintenance plan	44
9.1	Wheelset bearings subject to water ingress	44
9.2	Wheelsets having been subjected to a short circuit current (e.g. from falling overhead line equipment, etc.)	44
9.3	Detection by a trackside facility of a wheel circularity defect	44
9.4	Wheelsets loaded over the allowed limit	44
9.5	Hot axle box detection	45
9.5.1	General	45
9.5.2	Technical procedure	45
9.6	Derailment	45
9.7	Head-on collision	45
9.8	Lubricant leakage or loss from the axle box	46
9.9	Brake incident (detection of seized brake or discoloration)	46
9.10	Reporting after detection of a wheelset irregularity outside the maintenance plan	46
10	Equipment not subject to Directive 2008/57/EC	46
11	Summary table of requirements of this standard	46

Annex A (normative) Minimum database content for freight wagon wheelset traceability	47
A.1 Data categories for storage time	47
A.2 Minimum data to be collected	47
A.2.1 Boxed wheelset	47
A.2.2 Wheelset axle	49
A.2.3 Wheels	50
A.2.4 Bearings	51
A.2.5 Medium and heavy wheelset maintenance	51
A.2.6 Vehicle in which the boxed wheelset is mounted (not applicable for bogies with variable gauge) and in-service incidents (since applying traceability system)	52
A.3 Measures to be applied resulting from lack of traceability	52
Annex B (informative) Database content for the tractability of wheelsets of vehicles in the scope of TSI "Rolling stock - Locomotive and passenger rated vehicles" (TSI Loc & Pas)	54
B.1 Data categories for storage time	54
B.2 Minimum data to be collected	54
B.2.1 Boxed wheelset	54
B.2.2 Axle	56
B.2.3 Wheels	57
B.2.4 Bearings	58
B.2.5 Medium and heavy wheelset maintenance	58
B.2.6 Vehicle in which the boxed wheelset is mounted (not applicable for bogies with variable gauge) and in-service incidents (since applying traceability system)	59
B.3 Measures to be applied resulting from lack of traceability	60
Annex C (normative) Definition and illustration of defects	61
C.1 General	61
C.2 Defects for all types of wheel	61
C.2.1 Wheel flat	61
C.2.2 Metal build-up	62
C.2.3 Shelling, cavities	63
C.2.4 Scaling	63
C.2.5 Tread indentation	64
C.2.6 Isolated transverse cracking	64
C.2.7 Circularity defect	65
C.2.8 Spalling (thermal effects due to tread braking)	67
C.2.9 Rolling contact fatigue	68
C.2.10 Thermal cracks	68
C.2.11 Wheel tread roll-over	70
C.2.12 Damage to chamfered corner	70
C.2.13 Wheel tread - grooves and channels (or smooth edged circumferential grooves and sharp edged circumferential fluting)	71
C.2.14 False flange	72
C.2.15 Damage on the flange	74
C.2.16 Sharp-edged radial marks and radial defects on the internal face of the rim (FIJ)	75
C.2.17 Damage resulting from identification markings	76
C.2.18 Damage from lathe driving tools	77
C.2.19 Sharp-edged circumferential defects on the web or wheel centre	77
C.2.20 Sharp-edged radial defect on the web	78
C.2.21 Wheel web hole defects	78
C.2.22 Cracks in the wheel hub	79
C.3 Defects specific to wheel types	79
C.3.1 Deep sub-surface tread defect on monobloc wheels	79
C.3.2 Wheel web defects on monobloc wheels	80
C.3.3 Exceptional thermomechanical stressing in tyred wheels	82
C.4 Axle defects	82
C.4.1 Axle protection defect - Damage on the painting/coating	82
C.4.2 Corrosion	83
C.4.3 Circumferential defects	84

C.4.4	Notches and impact damage	86
C.4.5	Longitudinal defects	87
C.4.6	Damage in the interference fit zones	87
C.5	Axle box defects	88
C.6	Wheelset defects	89
C.6.1	General	89
C.6.2	Wheel distortion	89
C.6.3	In service axial or angular movement of a wheel or of one of the other components	90
C.6.4	Bent axle	91
Annex D (normative) Freight stock		92
Annex E (informative) Rim size without roll-over for equipment not subject to Directive 2008/57/EC		93
Annex F (normative) Definitions of Type A and B axles		94
Annex G (informative) Permissible circularity defects		97
Annex H (informative) Tyred wheels and resilient wheels		98
H.1	General	98
H.2	Marking of tyred wheels and resilient wheels	98
H.2.1	General	98
H.2.2	Tyre thickness of tyred wheels	99
H.3	Defects specific to tyred wheels	100
H.4	Verification of the electrical resistance during medium and heavy maintenance	101
Annex I (normative) Reference images for axle surface condition limits for off vehicle wheelset maintenance		102
I.1	General	102
I.2	Local and severe defect	102
I.3	Large and heavily corroded areas, strongly and uniformly pitted surface	103
I.4	Corrosion defects in abutment area and transition radii	104
Annex J (informative) NDT interval		105
J.1	General	105
J.2	Axle	105
J.3	Wheel	105
Annex K (informative) Summary of the requirements of this standard for in-service boxed wheelsets		106
Annex L (informative) Characteristics of narrow gauge wheelsets		108
Annex M (informative) Characteristics of Spanish and Portuguese gauge wheelsets		109
Annex N (informative) Characteristics of Finnish and Baltic Country Gauge Wheelsets		110
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC aimed to be covered		111
Bibliography		114