

DIN EN 16730:2016-09 (E)

Railway applications - Track - Concrete sleepers and bearers with under sleeper pads

| Contents | Page |
|--|-------------|
| European foreword | 5 |
| Introduction | 6 |
| 1 Scope | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 8 |
| 4 Symbols | 11 |
| 5 Design approval tests and routine tests | 12 |
| 5.1 General | 12 |
| 5.2 Summary of design approval tests and routine tests | 12 |
| 5.3 Tests of USP alone and of USP on concrete block | 14 |
| 5.3.1 Tensile strength of USP material | 14 |
| 5.3.2 Static and low frequency dynamic bedding modulus of USP on concrete block with GBP | 14 |
| 5.3.3 Static and low frequency dynamic bedding modulus of USP alone with GBP | 15 |
| 5.3.4 Higher frequency dynamic bedding modulus of USP on concrete block | 15 |
| 5.3.5 Fatigue test of USP on concrete block | 16 |
| 5.3.6 Fatigue test of USP on concrete block with GBP | 16 |
| 5.3.7 Capability for stacked stocking of sleepers with USP, testing by USP on a concrete block | 17 |
| 5.3.8 Effect of severe environmental conditions on USP on concrete block | 17 |
| 5.3.9 Resistance to other environmental parameters | 18 |
| 5.4 Tests of concrete sleepers and bearers without USP | 18 |
| 5.5 Tests of USP on concrete sleepers and bearers | 18 |
| 5.5.1 Dimensions and masses of sleepers and bearers with USP | 18 |
| 5.5.2 Bond strength by pull-out of USP on sleeper and bearer | 19 |
| 5.5.3 Fatigue test of USP on sleeper | 19 |
| 5.5.4 Environment and end of life | 20 |
| 6 Data to be supplied | 20 |
| 6.1 General | 20 |
| 6.2 Data supplied by the purchaser | 20 |
| 6.3 Data supplied by the supplier of sleeper with USP | 21 |
| 6.3.1 General | 21 |
| 6.3.2 Before the design approval tests | 21 |
| 6.3.3 After the design approval tests | 22 |
| 6.3.4 Prior to first start-up of production | 22 |
| 7 Rules for use of sleepers and bearers with USP | 22 |
| 8 Quality control | 22 |
| 9 Marking, labelling and packaging | 23 |
| Annex A (normative) Geometric Ballast Plate (GBP) | 24 |
| A.1 Design of the GBP | 24 |
| A.2 Material of GBP | 24 |

| | |
|---|-----------|
| Annex B (normative) USP on concrete block | 27 |
| B.1 Design of the USP on concrete block | 27 |
| B.2 Tolerances of USP on concrete block | 27 |
| Annex C (normative) Static and low frequency dynamic bedding modulus of USP on concrete block or of USP alone with GBP | 29 |
| C.1 General | 29 |
| C.2 Static test procedure | 29 |
| C.2.1 Principle | 29 |
| C.2.2 Apparatus | 29 |
| C.2.3 Procedure | 30 |
| C.2.4 Test report | 32 |
| C.3 Low frequency dynamic test procedure | 32 |
| C.3.1 Principle | 32 |
| C.3.2 Apparatus | 33 |
| C.3.3 Procedure | 33 |
| C.3.4 Test report | 35 |
| Annex D (normative) Fatigue test of USP on concrete block | 36 |
| D.1 Principle | 36 |
| D.2 Apparatus | 36 |
| D.3 Procedure | 37 |
| D.4 Test report | 39 |
| Annex E (normative) Bond strength by pull-out of USP on sleeper and bearer | 40 |
| E.1 Principle | 40 |
| E.2 Apparatus | 40 |
| E.3 Procedure | 40 |
| E.4 Test report | 41 |
| Annex F (normative) Data sheet | 43 |
| F.1 Data Sheet 1 (for USP Materials) | 43 |
| F.2 Data Sheet 2 (for sleepers and bearers with USP) | 44 |
| Annex G (informative) General design approval tests and the routine tests for the USP and the sleeper with USP | 45 |
| Annex H (informative) Higher frequency dynamic vertical bedding modulus of USP on concrete block | 46 |
| H.1 Principle | 46 |
| H.2 Test arrangement | 46 |
| H.2.1 Test arrangement for the direct method | 46 |
| H.2.2 USP on concrete block | 48 |
| H.2.3 Ambient Test temperature | 48 |
| H.2.4 Vibration test velocity | 48 |
| H.3 Test procedure and evaluation | 48 |
| H.3.1 General | 48 |
| H.3.2 Loss factor | 48 |
| H.3.3 Higher frequency dynamic stiffening ratio H (80 Hz) | 49 |
| H.4 Test report | 49 |
| Annex I (informative) Fatigue test of USP on concrete block with GBP | 50 |
| I.1 Principle | 50 |
| I.2 Apparatus | 50 |

| | | |
|---|--|-----------|
| I.3 | Procedure | 51 |
| I.4 | Test report | 52 |
| Annex J (informative) Capability of stacked storage of sleepers with USP | | 54 |
| J.1 | Principle | 54 |
| J.2 | Apparatus | 54 |
| J.3 | Procedure | 55 |
| J.4 | Test report | 56 |
| Annex K (informative) Static and low frequency dynamic bedding modulus of USP on concrete sleeper or bearer with GBP | | 57 |
| K.1 | General | 57 |
| K.2 | Static test procedure | 57 |
| K.2.1 | Principle | 57 |
| K.2.2 | Apparatus | 57 |
| K.2.3 | Procedure | 58 |
| K.2.4 | Test report | 60 |
| K.3 | Low frequency dynamic test procedure | 61 |
| K.3.1 | Principle | 61 |
| K.3.2 | Apparatus | 61 |
| K.3.3 | Procedure | 61 |
| K.3.4 | Test report | 63 |
| Annex L (informative) Fatigue test on USP on sleeper | | 64 |
| L.1 | Principle | 64 |
| L.2 | Apparatus | 64 |
| L.3 | Procedure | 65 |
| L.4 | Test report | 67 |
| Annex M (informative) Alternative fatigue test on USP on sleeper | | 69 |
| M.1 | Principle | 69 |
| M.2 | Apparatus | 69 |
| M.3 | Procedure | 70 |
| M.4 | Test report | 71 |
| Annex N (informative) Effect of severe environmental conditions on USP on concrete block | | 73 |
| N.1 | Principle | 73 |
| N.2 | Apparatus | 73 |
| N.3 | Procedure | 73 |
| N.4 | Test report | 75 |
| Bibliography | | 76 |