DIN EN 16272-4:2016-12 (E)

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - In situ values of sound diffraction under direct sound field

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Symbols and abbreviations 9

5 Sound diffraction index difference measurements 10
5.1 General principle 10
5.2 Dimensions and specifications 15
5.2.1 Added devices 15
5.2.2 Reference walls 15
5.2.3 In situ tests 16
5.3 Positions of the sound source 16
5.4 Position of the microphone(s) 16
5.5 Free-field measurements 17
5.6 Measured quantity 18
5.7 Measuring equipment 18
5.7.1 Components of the measuring system 18
5.7.2 Sound source 20
5.7.3 Test signal 20
5.8 Data processing 20
5.8.1 Calibration 20
5.8.2 Sample rate 21
5.8.3 Background noise 21
5.8.4 Measurement points 21
5.8.5 Adrienne temporal window 21
5.8.6 Placement of the Adrienne temporal window 22
5.8.7 Low frequency limit and sample size 24
5.9 Positioning of the measuring equipment 24
5.9.1 Selection of the measurement positions 24
5.9.2 Reflecting objects 25
5.9.3 Safety considerations 25
5.10 Sound diffraction index difference 25
5.11 Sample surface and meteorological conditions 25
5.11.1 Condition of the sample surface 25
5.11.2 Wind 26
5.11.3 Air temperature 26

6 Measurement uncertainty 26

7 Measuring procedure 26

8 Test report 27

8.1 Expression of results 27
8.2 Further information 27

Annex A (informative) Indoor measurements for product qualification 29

A.1 General 29
A.2 Parasitic reflections 29
A.3 Reverberation time of the room 29

Annex B (informative) Measurement uncertainty 30

B.1 General 30
B.2 Expression for the calculation of sound diffraction index 30
B.3 Contributions to measurement uncertainty 31
B.4 Expanded uncertainty of measurement 32
B.5 Measurement uncertainty based upon reproducibility data 32

Bibliography 33