

DIN EN 13848-5:2017-10 (E)

Railway applications - Track - Track geometry quality - Part 5: Geometric quality levels - Plain line, switches and crossings

| Contents | | Page |
|--|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Symbols and abbreviations | 5 |
| 5 | General Considerations | 5 |
| 6 | Assessment of track geometry quality | 6 |
| 7 | Immediate action limits | 7 |
| 7.1 | Introductory remarks | 7 |
| 7.2 | Track gauge | 8 |
| 7.3 | Longitudinal level | 9 |
| 7.4 | Cross level | 10 |
| 7.5 | Alignment | 10 |
| 7.6 | Twist | 11 |
| 8 | Alert and intervention limit | 12 |
| 8.1 | Introduction | 12 |
| 8.2 | Mean track gauge over 100 m | 12 |
| Annex A (informative) Relative importance of the various parameters | | 14 |
| A.1 | Track-vehicle system | 14 |
| A.2 | Influence of track geometry parameters on vehicle behaviour and safety | 15 |
| A.3 | Other criteria | 15 |
| Annex B (informative) Alert and intervention limits | | 17 |
| B.1 | Introduction | 17 |
| B.2 | Alert limit and intervention limit | 17 |
| B.2.1 | Track gauge | 17 |
| B.2.2 | Longitudinal level | 18 |
| B.2.3 | Cross level | 18 |
| B.2.4 | Alignment | 19 |
| B.2.5 | Twist | 19 |
| Annex C (normative) Twist limits for nominal track gauge of 1668 mm | | 21 |
| Annex D (informative) A-Deviations | | 22 |
| Annex ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive 2008/57/EC | | 23 |
| Bibliography | | 25 |