

# DIN CEN/TR 17039:2018-08 (E)

Railway applications - Technical Report about the revision of EN 14363; English  
version CEN/TR 17039:2017

---

<b>Contents</b>		<b>Page</b>
European foreword .....		5
1	Scope .....	6
2	Members of the different drafting groups for the revision of EN 14363 .....	6
3	Changes to the scope .....	7
3.1	Scope extension .....	7
3.2	Limitation .....	7
3.3	Clarification .....	8
3.4	Shifted to other sections .....	8
4	Fault modes .....	8
4.1	What was changed? .....	8
4.2	Why was it changed? .....	9
4.3	Comments raised in the CRM process and how they were addressed .....	9
5	Load conditions for testing .....	9
6	First stage assessment .....	10
6.1	General .....	10
6.2	Safety against derailment on twisted track .....	10
6.3	Safety against derailment under longitudinal compressive forces in S-shaped curves .....	12
6.4	Evaluation of the torsional coefficient of a car body .....	12
6.5	Determination of displacement characteristics .....	12
6.6	Loading of the diverging branch of a switch .....	13
6.7	Running safety in curved crossings for vehicles with small wheels .....	14
7	Statistical analysis and multiple regression .....	14
7.1	Background .....	14
7.2	Relationship of assessment parameters and input variables .....	14
7.3	Assessment methods .....	16
7.4	Assessment by statistical methods in EN 14363 .....	16
7.4.1	General .....	16
7.4.2	One-dimensional method .....	16
7.4.3	Two-dimensional method .....	24
7.4.4	Multiple regression .....	28
7.5	Regression assumptions .....	31
8	Recalculation of Y/Q (7.6.2.2.5) .....	32
8.1	What was changed .....	32
8.2	Why was it changed .....	33
8.3	Any references to useful background .....	33
8.4	What were the options, what was rejected and why? .....	33
9	Track loading parameters .....	36
10	Rail surface damage quantity Tqst .....	36
10.1	What was changed .....	36
10.2	Why was it changed .....	36
10.3	Approach .....	37

10.4	Derivation and definition of Tqst .....	38
CEN/TR 17039:2017 (E)	10.5 Measurable quantities .....	39
10.6	Limit values .....	39
10.7	Verification from tests .....	40
11	Replacing of limit values of ride characteristics by informative guidance for assessment	40
11.1	General .....	40
11.2	Removing limit values for quasi-static lateral acceleration .....	41
11.3	Revision of accelerometer positions in the car body of freight vehicles .....	42
12	Track geometric quality and coordination with WG 28 .....	42
12.1	Background .....	42
12.2	Joint Survey Group WG 10 / WG 28 .....	44
12.3	DynoTRAIN project .....	45
12.4	Use of 50 % and / or 90 % levels .....	45
12.5	Changes from EN 14363:2005 and UIC 518:2009 .....	45
12.6	Speed range used for Track Quality assessment .....	46
12.7	Wavelength Ranges .....	46
12.8	Requirements in different zones .....	47
12.9	Topics discussed but not changed .....	47
13	Contact conditions .....	47
13.1	Equivalent conicity .....	47
13.1.1	Summary of requirements of EN°14363:2005 .....	47
13.1.2	Summary of requirements of UIC Leaflet 518:2009 .....	48
13.1.3	Changes in EN 14363:2016 .....	48
13.2	Background information about investigations carried out in the DynoTRAIN project .....	49
13.3	Radial steering index (RSI) .....	54
13.3.1	Summary of requirements of EN°14363:2005 .....	54
13.3.2	Summary of requirements of UIC Leaflet 518:2009 .....	54
13.3.3	Changes in EN°14363:2016 .....	55
13.3.4	Background information about the radial steering index .....	55
14	Special vehicles .....	58
15	Simulation .....	59
15.1	General .....	59
15.2	Model validation .....	60
15.2.1	Principle of model validation .....	60
15.2.2	Evaluations to carry out model validation .....	60
15.2.3	Independent review .....	61
15.2.4	Validation proposal from DynoTRAIN .....	61
15.2.5	Efficiency of the usage of stationary tests .....	62
15.3	Fields and conditions for application of simulation .....	62
15.3.1	Introduction .....	62
15.3.2	Definitions of reference and modified vehicle .....	62
15.3.3	Scope of permitted modifications .....	63
15.3.4	Requirements regarding the modification of a validated model .....	63
15.3.5	Evaluation of estimated values .....	64
15.3.6	Application field: Extension of the range of test conditions .....	64
15.3.7	Application field: Approval of vehicle modification .....	64
15.3.8	Application field: Approval of new vehicles by comparison with a reference vehicle .....	65
15.3.9	Application field: Investigation of dynamic behaviour in case of fault modes .....	65
15.4	Input data for simulation .....	65
15.4.1	Introduction .....	65
15.4.2	Track layout .....	65
CEN/TR 17039:2017 (E)	15.4.3 Track irregularity data .....	66
15.4.4	Frequency / wavelength content .....	66
15.4.5	Requirements for variation in input conditions .....	66

16	Extension of acceptance (Annex U) .....	66
17	Topics discussed but postponed for future revisions .....	68
17.1	General .....	68
17.2	Y/Q .....	68
17.3	Tqst .....	68
17.4	Bqst and Bmax .....	68
17.5	Ya,max .....	68
17.6	Introduction of high frequency contents to the Q-force limits .....	68
17.7	Track geometry .....	69
17.8	Compatibility with track conditions outside the test conditions .....	69
17.9	WHEEL RAIL Geometric contact conditions .....	69
17.10	Cyclic top .....	70
17.11	Over-speed and over Cant deficiency testing .....	70
17.12	General points .....	70
18	Influence of the revision of EN 14363 on current TSIs .....	71
18.1	General .....	71
18.2	Letter to ERA .....	71
18.3	Annex 1 to letter to ERA .....	71
	<b>Annex A (informative) Guideline for presentation of results from multiple regression .....</b>	<b>76</b>
A.1	Introduction and purpose .....	76
A.2	Principles .....	76
A.3	Example .....	77
	<b>Bibliography .....</b>	<b>80</b>