

DIN EN 12927:2019-08 (E)

Safety requirements for cableway installations designed to carry persons - Ropes

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 9 |
| 4 | Symbols and abbreviated terms | 12 |
| 5 | Requirements | 13 |
| 6 | Safety principles | 13 |
| 6.1 | General | 13 |
| 6.2 | Hazard scenarios | 13 |
| 6.3 | Safety measures | 15 |
| 7 | Selection criteria for ropes and their end fixing | 16 |
| 7.1 | Ropes | 16 |
| 7.2 | Fibre ropes | 18 |
| 7.2.1 | General | 18 |
| 7.2.2 | Fibre ropes for carrying-hauling ropes (for ski-tows) | 18 |
| 7.2.3 | Fibre ropes for towing cord | 18 |
| 7.3 | Rope re-use | 18 |
| 7.4 | End fixings (excluding long splice) | 19 |
| 8 | Safety factors | 19 |
| 8.1 | General | 19 |
| 8.2 | Tensile safety | 19 |
| 8.3 | Diameter ratio | 21 |
| 8.4 | Transverse force ratio | 22 |
| 8.4.1 | Roller transverse force ratio | 22 |
| 8.4.2 | Carrier transverse force ratio | 22 |
| 9 | Discard criteria | 23 |
| 9.1 | General | 23 |
| 9.2 | Main body of the rope and long splice | 23 |
| 9.2.1 | Ropes examined by magnetic rope testing (MRT) | 23 |
| 9.2.2 | Ropes examined by visual inspection (VI) | 23 |
| 9.3 | Tension ropes | 24 |
| 9.4 | Local deterioration | 24 |
| 9.4.1 | General | 24 |
| 9.4.2 | Main body of the rope | 24 |
| 9.4.3 | Splice | 25 |
| 9.5 | Rope at end fixing | 25 |
| 9.5.1 | Filled socket | 25 |
| 9.5.2 | Other end fixing | 26 |
| 10 | Storage, handling, transportation and installation (including tensioning, connecting and/ or splicing) | 26 |
| 10.1 | General | 26 |
| 10.2 | Storage | 26 |

| | | |
|---------|---|----|
| 10.3 | Handling and transportation | 26 |
| 10.4 | Installation (including tensioning, connecting and/or splicing) | 27 |
| 10.4.1 | General | 27 |
| 10.4.2 | Measurements, adjustments and records | 28 |
| 11 | Splicing of 6 stranded steel wire ropes | 28 |
| 11.1 | General | 28 |
| 11.2 | Splice geometry | 28 |
| 11.2.1 | General | 28 |
| 11.2.2 | Splice dimensions | 29 |
| 11.2.3 | Documentation | 29 |
| 12 | End fixing | 29 |
| 12.1 | General | 29 |
| 12.2 | Design | 29 |
| 12.3 | Execution and conformity | 30 |
| 12.4 | Filled socket | 30 |
| 12.4.1 | General | 30 |
| 12.4.2 | Design | 31 |
| 12.4.3 | Manufacture | 31 |
| 12.4.4 | Socketing execution | 31 |
| 12.5 | Clamp socket | 32 |
| 12.5.1 | General | 32 |
| 12.5.2 | Design | 33 |
| 12.5.3 | Manufacture | 33 |
| 12.5.4 | Execution | 33 |
| 12.6 | Drum (Fixing drum and anchor drum) | 34 |
| 12.7 | Bolted clamp | 34 |
| 12.7.1 | Design | 34 |
| 12.7.2 | Manufacture | 35 |
| 12.7.3 | Execution and maintenance | 35 |
| 12.8 | Wedge socket | 36 |
| 12.8.1 | Symmetrical | 36 |
| 12.8.2 | Asymmetrical | 36 |
| 12.9 | Spliced eye | 36 |
| 12.10 | Gripped eye | 36 |
| 12.11 | Ferrule secured eye | 36 |
| 12.12 | Lever winch | 36 |
| 13 | Maintenance | 36 |
| 13.1 | General | 36 |
| 13.2 | Servicing | 44 |
| 13.2.1 | General | 44 |
| 13.2.2 | Rope cleaning and lubrication | 44 |
| 13.2.3 | Relocation of carrying ropes, fixed grips on monocable aerial ropeways and signal ropes | 44 |
| 13.2.4 | Relocation of signal ropes | 45 |
| 13.2.5 | End fixing | 45 |
| 13.2.6 | Shortening of rope loops | 45 |
| 13.2.7 | End fixing of towing cords | 45 |
| 13.3 | Inspection | 45 |
| 13.3.1 | General | 45 |
| 13.3.2 | Personnel requirements | 46 |
| 13.3.3 | Initial inspection | 46 |
| 13.3.4 | Periodical inspection | 46 |
| 13.3.5 | Extraordinary inspection | 46 |
| 13.3.6 | Visual inspection (VI) | 46 |
| 13.3.7 | Inspection types | 47 |
| 13.3.8 | Optical inspection devices (OID) | 47 |
| 13.3.9 | Measurements | 47 |
| 13.3.10 | Magnetic rope testing | 49 |
| 13.3.11 | Radiographic testing | 49 |

| | | |
|---|--|----|
| 13.3.12 | Report | 49 |
| 13.3.13 | Rope indicators | 49 |
| 13.4 | Repair | 50 |
| 13.4.1 | General | 50 |
| 13.4.2 | Stranded rope | 50 |
| 13.4.3 | Locked coil rope | 50 |
| 13.4.4 | Anchor drum repair | 51 |
| 14 | Magnetic rope testing (MRT) | 51 |
| 14.1 | General | 51 |
| 14.2 | Instrumentation | 51 |
| 14.2.1 | Function and operational principles of magnetic flux leakage instruments | 51 |
| 14.2.2 | Test head | 52 |
| 14.2.3 | Visual display unit and permanent recording instrument | 52 |
| 14.3 | Test procedure | 52 |
| 14.3.1 | Personnel | 52 |
| 14.3.2 | Setting up | 52 |
| 14.3.3 | Test execution | 53 |
| 14.3.4 | Interpretation of results | 53 |
| 14.3.5 | Instrument verification | 54 |
| 15 | Fire protection and fire fighting | 55 |
| Annex A (informative) Guidelines for executing visual inspection type "A" | | 56 |
| Annex B (informative) Magnetic flux density | | 57 |
| Annex C (informative) Magnetic rope testing - Personnel qualifications levels | | 58 |
| Annex D (informative) Bolted clamp - Calculation of slipping force | | 60 |
| Annex E (informative) Determination of intervals related to visual inspections | | 61 |
| E.1 | General | 61 |
| E.2 | Operational conditions | 61 |
| E.2.1 | Bendings of stranded ropes | 61 |
| E.2.2 | Number of passages of rollers per year for locked coil ropes | 61 |
| E.3 | Operating personnel | 62 |
| E.4 | Carriers related conditions | 62 |
| E.5 | Cableway configuration | 63 |
| E.6 | Environmental conditions | 63 |
| E.7 | Final evaluation and result | 63 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Regulation (EU) 2016/424 on "Cableway installations" aimed to be covered | | 65 |