

DIN EN 16186-8:2022-06 (E)

Railway applications - Driver's cab - Part 8: Tram vehicle layout and access

Contents		Page
European Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Symbols and abbreviations	7
5	Access, egress and doors	7
5.1	General	7
5.1.1	External steps and handrails	7
5.1.2	Access and security	7
5.1.3	Door handles	8
5.1.4	Threshold	8
5.1.5	Ergonomics	8
5.1.6	External doors	8
5.1.7	Internal doors giving access to the driver's cab	9
6	Floor and flooring	10
6.1	Floor surface criteria	10
6.2	Steps	10
7	Windows and glazing	11
7.1	Mechanical characteristics of glass	11
7.2	Operation of opening windows	11
8	Emergency	11
8.1	Driver's cab emergency exits	11
8.1.1	General	11
8.1.2	Minimum escape route	11
8.1.3	Emergency exit opening	11
8.2	Emergency egress from seat	12
8.2.1	Seat design for escape	12
8.2.2	Escape from seat assessment criteria	12
9	Layout	12
9.1	General	12
9.2	Prevention of occupational injuries	13
9.2.1	General	13
9.2.2	Exposed edges	13
9.3	Comfort angles	14
9.4	Interior space	16
9.5	Driver's desk	16
9.6	Footrest	16
9.7	Storage space	17
9.7.1	General	17
9.7.2	Storage of personal belongings	17
9.7.3	Emergency equipment	17
9.8	Seats	17
9.8.1	General	17

9.8.2	Driver's seat	17
9.8.3	Additional seats	19
9.9	Surface finish	19
9.10	Privacy shield	19
10	Lighting	20
11	Marking and labelling in driver's cab	20
Annex A (normative) Driver's seat dimensions and driver's seat integration		21
Annex B (normative) Minimum leg clearance		25
Annex C (normative) Mandatory labels		26
Bibliography		27