DIN EN 17636:2023-12 (E)

Railway applications - Infrastructure - Track alignment design parameters - Urban rail

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Symbols and abbreviations 9

5 General 10
5.1 Background 10
5.2 Line categories 10
5.3 Alignment characteristics 11

6 Limits for 1 435 mm and 1 000 mm nominal track gauge 13
6.1 Horizontal radius R 13
6.2 Applied cant D 13
6.3 Cant deficiency I 14
6.4 Cant excess E 15
6.5 Length of cant transition DL and/or transition curve in the horizontal plane LK 15
6.5.1 General 15
6.5.2 Length of linear cant transition and/or clothoid 16
6.6 Cant gradient d / dD s 16
6.7 Rate of change of cant d / dD t 17
6.8 Rate of change of cant deficiency d / dI t 17
6.9 Length of constant cant between two linear cant transitions Li 18
6.10 Abrupt change of horizontal curvature 18
6.11 Abrupt change of cant deficiency I 18
6.12 Length between two abrupt changes of horizontal curvature Lc 19
6.13 Length between two abrupt changes of cant deficiency Ls 20
6.14 Track gradient p 20
6.15 Length of constant track gradient Lg 21
6.16 Vertical radius Rv 21
6.17 Length of vertical curve Lv 23
6.18 Abrupt change of track gradient p 23

Annex A (normative) Rules for converting parameter values for nominal track gauges other than 1 435 mm 24

A.1 General 24
A.2 Symbols and abbreviations 24
A.3 Basic assumptions and equivalence rules 26
A.3.1 General 26
A.3.2 Basic formulae 26
A.3.3 Basic data 27
A.4 Detailed conversion rules 27
A.4.1 General 27
A.4.2 Cant D1 (6.2) 27
A.4.3 Cant deficiency I1 (6.3) 29
A.4.4 Cant excess E1 (6.4) 30

A.4.5 Length of cant transition LD and transition curve in the horizontal plane LK (6.5) 31
A.4.6 Cant gradient dD1/dt (6.6) 31
A.4.7 Rate of change of cant 1d / dD t (6.7) 32
A.4.8 Rate of change of cant deficiency dI1/dt (6.8) 33
A.4.9 Abrupt change of curvature and abrupt change of cant deficiency I1 (6.10 and 6.11) 34
A.4.10 Other parameters (6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16, 6.17 and 6.18) 34

Annex B (normative) Three-dimensional track geometry with regards to resulting cant gradient and resulting vertical radius 35

B.1 General considerations regarding three-dimensional track geometry 35
B.2 Angular twist TA and resulting cant gradient (dD/ds)r 35
B.2.1 Calculation of resulting cant gradient (dD/ds)r where cant is applied by lifting one rail / 2D and lowering the other rail / 2D 35
B.2.2 Calculation of resulting cant gradient (dD/ds)r when cant is applied by lifting one rail D .. 36
B.3 Resulting vertical radius (Rv)r 36

Annex C (informative) The relations between cant deficiency, non-compensated lateral acceleration and related parameters 38

C.1 Introduction 38
C.2 Applied cant and roll angle 38
C.3 Equilibrium cant 39
C.4 Cant deficiency and non-compensated lateral acceleration 40
C.5 Applications 41

Annex D (normative) Sign rules for calculation of D , I and p 42

D.1 General regarding the sign rules 42
D.2 Sign rules for calculation of D 42
D.3 Sign rules for calculation of I 42
D.4 Sign rules for calculation of p 43

Annex E (normative) Lengths of intermediate elements Lc between small radius curves in opposite directions 45

E.1 General 45
E.2 Lengths of intermediate elements Lc for Line Category A1435 45
E.3 Lengths of intermediate elements Lc for Line Category B1435 and C1000 46

Bibliography 48