DIN EN 15313:2024-12 (E)

Railway applications - In-service wheelset operation requirements - In-service and off-vehicle wheelset maintenance

Contents

Page

European foreword 6

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms, definitions, symbols and abbreviated terms 9

4 Maintenance 11
4.1 General 11
4.2 Maintenance organization 11
4.2.1 Maintenance organization plan 11
4.2.2 Maintenance plan 11
4.2.3 Service experience 12
4.2.4 Traceability - storage - transportation 12
4.3 Equipment and systems 14
4.4 Staff certification and competence 14
4.5 Qualification of an undertaking for the maintenance of in-service or off-vehicle wheelsets 14

5 Definition and illustrations of a wheelset, its associated components and defects 15
5.1 Definition and illustrations of a wheelset 15
5.1.1 Wheelset 15
5.1.2 Axle 17
5.1.3 Wheel 18
5.1.4 Axlebox 19
5.2 Functional references of the rail-wheel interface 20
5.2.1 Wheelset functional references 20
5.2.2 Wheel functional references 21
5.3 Definitions and illustrations of defects 21

6 Requirements and operations 22
6.1 General 22
6.2 Requirements 22
6.2.1 In-service limit dimensions and positions 22
6.2.2 Special maintenance action for freight wagon axles according to axle load 26
6.2.3 Maintenance decision criteria for in-service wheels for all types of wheel 27
6.2.4 Maintenance decision criteria for in-service wheels for specific wheel types 30
6.2.5 Damage acceptance limits for axle bodies 31
6.2.6 Criteria for axlebox (C.5) 32
6.2.7 Criteria on wheelsets 32
6.2.8 Specific requirements for tyred wheels and resilient wheels 33
6.2.9 Limit value for axle wheel seat diameter 34
6.3 Reprofiling operation 34
6.4 Dimensions after reprofiling 35
6.4.1 Front-to-front dimension "a2" 35
6.4.2 Diameter difference between wheels on the same axle 35
6.4.3 Limit values of radial run-out as a function of the maximum operating speed authorized for the vehicle 35

6.4.4 Wheel axial run-out as a function of the maximum operating speed authorized for the vehicle ... 35
6.4.5 Parts of the tread that are not re-profiled ... 35
6.4.6 Radial marks and radial defects on the internal side of the rim ... 36
6.5 Maintenance operations, examinations and inspections ... 36
6.5.1 General ... 36
6.5.2 Detection of tread defects ... 36
6.5.3 Detection of thermal damage on the wheel rim or tyre ... 36
6.5.4 Detection of wheel tread roll-over ... 37
6.5.5 Detection of damage to chamfered corner and flange ... 37
6.5.6 Detection of damage resulting from identification markings ... 37
6.5.7 Detection of defects on the external and internal face of the rim ... 37
6.5.8 Verification of web integrity ... 37
6.5.9 Verification of hub integrity ... 37
6.5.10 Verification of rim integrity - Detection of deep sub-surface tread defects ... 38
6.5.11 Detection of thermal defects on the web of a wheel used as a braking surface ... 38
6.5.12 Detection of overheating affecting the wheel rim-web transition on monobloc wheels ... 38
6.5.13 Verification of axle surface integrity ... 38
6.5.14 Detection of damage caused by corrosion ... 41
6.5.15 Detection of circumferential defects around the whole circumference ... 41
6.5.16 Detection of circumferential defects in a singular section of the circumference ... 41
6.5.17 Detection of notches and impact damage ... 41
6.5.18 Detection of longitudinal defects on axles ... 41
6.5.19 Detection of damage in interference fit zones ... 41
6.5.20 Verification after rectification ... 41
6.5.21 Verification of residual magnetism ... 41
6.5.22 Lubrication operation ... 41
6.5.23 Checking for axlebox defects ... 42
6.5.24 Verification of wheelset electrical resistance after heavy maintenance of wheelsets ... 42
6.6 Requirements for additional maintenance equipment and operations ... 42

7 In-service wheelset maintenance ... 42
7.1 Maintenance plan ... 42
7.2 Wheelset protection during vehicle and bogie cleaning ... 42

8 Off-vehicle wheelset maintenance ... 43
8.1 Maintenance plan ... 43
8.2 Key operations for off-vehicle wheelset maintenance ... 43
8.3 Off-vehicle wheelset cleaning ... 44
8.4 NDT Interval ... 44

9 Action to be taken on any wheelset after an incident in service or when not covered by the maintenance plan ... 44
9.1 Wheelset bearings subject to water ingress ... 44
9.2 Wheelsets having been subjected to a short circuit current (e.g. from falling overhead line equipment, etc.) ... 44
9.3 Detection of a wheel circularity defect by a trackside facility or an onboard monitoring system ... 44
9.4 Wheelsets loaded over the allowed limit ... 44
9.5 Hot axlebox detection ... 45
9.5.1 General ... 45
9.5.2 Technical procedure ... 45
9.6 Derailment ... 45
9.7 Head-on collision ... 46
9.8 Lubricant leakage or loss from the axlebox ... 46
9.9 Thermal overloaded wheels, brake incident (detection of seized brake or discoloration) ... 46
9.10 Reporting after detection of a wheelset irregularity outside the maintenance plan ... 46

10 Equipment not subject to Directive (EU) 2016/797 ... 46

11 Summary table of requirements of this document ... 46

Annex A (normative) Minimum database content for freight wagon wheelset traceability ... 47

A.1 Data categories for storage time 47
A.2 Minimum data to be collected 47
A.3 Measures to be applied resulting from lack of traceability 52

Annex B (informative) Database content for the traceability of wheelsets of vehicles in the scope of TSI "Rolling stock - Locomotive and passenger rated vehicles" (TSI Loc and Pas) 54

B.1 Data categories for storage time 54
B.2 Minimum data to be collected 54
B.3 Measures to be applied resulting from lack of traceability 59

Annex C (normative) Definition and illustration of defects 61

C.1 General 61
C.2 Defects for all types of wheel 61
C.3 Defects specific to wheel types 83
C.4 Axle defects 87
C.5 Axlebox defects 92
C.6 Wheelset defects 93

Annex D (normative) Freight stock 96

Annex E (informative) Rim size without roll-over for equipment not subject to Directive (EU) 2016/797 97

Annex F (normative) Definitions of Type A and B axles 98

Annex G (informative) Permissible circularity defects 101

Annex H (informative) Tyred wheels and resilient wheels 102

H.1 General 102
H.2 Marking of tyred wheels and resilient wheels 102
H.3 Tyre thickness of tyred wheels 103
H.4 Defects specific to tyred wheels 104
H.5 Verification of the electrical resistance during medium and heavy maintenance 104

Annex I (normative) Reference images for axle surface condition limits for off-vehicle wheelset maintenance 105

I.1 General 105
I.2 Local and severe defect 105
I.3 Large and heavily corroded areas, strongly and uniformly pitted surface 106
I.4 Corrosion defects in abutment area and transition radii 106

Annex J (informative) NDT interval 108

J.1 General 108
J.2 Axle 108
J.3 Wheel 108

Annex K (informative) Summary of the requirements of this standard for in-service boxed wheelsets 109

Annex L (informative) Characteristics of narrow gauge wheelsets 111

Annex M (informative) Characteristics of Spanish and Portuguese gauge wheelsets 112

Annex N (informative) Characteristics of Finnish and Baltic country gauge wheelsets 113

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive (EU) 2016/797 aimed to be covered 114

Bibliography 116