

# DIN EN 15839:2024-12 (E)

## Railway applications - Testing and simulation for the acceptance of running characteristics of railway vehicles - Running safety under longitudinal compressive force

---

| <b>Contents</b>   |   | <b>Page</b> |
|---|---|-------------|
| European foreword .....   |   | 4           |
| Introduction .....  |   | 6           |
| 1   | Scope .....   | 7           |
| 2   | Normative references .....  | 8           |
| 3   | Terms and definitions .....   | 8           |
| 4   | Deviations from requirements .....  | 10          |
| 5   | Proof of the endurable longitudinal compressive force .....   | 10          |
| 5.1   | Assessment of endurable longitudinal compressive force .....  | 10          |
| 5.2   | Required endurable longitudinal compressive force for use in conventional trains 10 5.3<br>Assessment of endurable longitudinal compressive force for use in high-capacity trains | 11          |
| 5.4   | Assessment of endurable longitudinal compressive force for vehicles equipped with<br>centre couplers .....  | 11          |
| 5.5   | Special vehicle layout .....  | 11          |
| 5.5.1   | Permanently coupled units consisting of 2-axle wagons with standard ends or diagonal<br>buffers .....   | 11          |
| 5.5.2   | Permanently coupled units with bar couplers .....   | 12          |
| Annex A (normative) Symbols .....   |   | 13          |
| Annex B (normative) Conditions for the execution and evaluation of propelling tests for the<br>determination of the endurable longitudinal compressive force of vehicles with side<br>buffers ..... |   | 14          |
| B.1   | Test track .....  | 14          |
| B.2   | Test train .....  | 14          |
| B.2.1   | Standard configuration .....  | 14          |
| B.2.2   | Supplementary configuration for 2-axle vehicles with LoB 15,75 m .....  | 16          |
| B.3   | Execution of the tests .....  | 16          |
| B.4   | Measured values .....   | 17          |
| B.4.1   | Measurements during the tests .....   | 17          |
| B.4.2   | Other measurements .....  | 18          |
| B.5   | Used criteria for the evaluation of the endurable longitudinal compressive force .....  | 18          |
| B.6   | Analysis .....  | 18          |
| B.7   | Documentation of results .....  | 19          |
| B.7.1   | General .....   | 19          |
| B.7.2   | Characteristics of the track on which the tests were carried out .....  | 20          |
| B.7.3   | Characteristics of the test vehicle .....   | 20          |
| B.7.4   | Test results .....  | 20          |
| Annex C (informative) Vehicles incorporated in conventional trains: Conditions for dispensation<br>from the assessment of running safety under longitudinal compressive force .....                 |   | 21          |
| C.1   | General .....   | 21          |

|              |  |    |
|--------------|--|----|
| C.2          | 2-axle wagons .....  | 21 |
| C.3          | Wagons with two 2-axle bogies .....  | 23 |
| C.4          | Wagons with 3-axle bogies .....  | 26 |
| C.5          | Railbound construction and maintenance machines .....  | 27 |
| <br>         |  |    |
| Annex D      | (informative) Conventional trains: Design characteristics of standardized interfaces of permanent coupled units for dispensation from the assessment of running safety under longitudinal compressive force - Specification of interface with diagonal buffers ..... | 29 |
| <br>         |  |    |
| Annex E      | (informative) Requirements for the use of simulations as proof for endurable longitudinal compressive force .....  | 30 |
| <br>         |  |    |
| E.1          | Introduction .....   | 30 |
| E.2          | State of the art for the heavy rail system in ENs related to running dynamics .....  | 30 |
| E.3          | Modelling for simulations .....  | 30 |
| E.3.1        | General .....  | 30 |
| E.3.2        | Intermediate wagons and trailing flanking wagon .....  | 31 |
| E.3.3        | Leading flanking wagon .....   | 32 |
| E.3.4        | Test track .....   | 32 |
| E.4          | Validation of the model .....  | 32 |
| E.5          | Performance of simulations .....   | 33 |
| E.5.1        | Required parameters (friction, track, speed etc) .....   | 33 |
| E.5.2        | Criteria applied for evaluation .....  | 33 |
| <br>         |  |    |
| Annex F      | (informative) Scenarios for the assessment of endurable longitudinal compressive force of a vehicle incorporated in a high-capacity train .....  | 34 |
| <br>         |  |    |
| Annex G      | (informative) Vehicle incorporated in a high-capacity trains: conditions for dispensation from the assessment of running safety under longitudinal compressive force .....   | 36 |
| <br>         |  |    |
| G.1          | Introduction .....   | 36 |
| G.2          | Wagons with 2 bogies .....   | 36 |
| G.3          | Articulated wagons with 3 bogies .....   | 37 |
| <br>         |  |    |
| Annex H      | (informative) Vehicles with centre couplers .....  | 38 |
| <br>         |  |    |
| Bibliography | .....  | 39 |