

# DIN EN 15839:2024-12 (E)

## Railway applications - Testing and simulation for the acceptance of running characteristics of railway vehicles - Running safety under longitudinal compressive force

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		6
1	Scope .....	7
2	Normative references .....	8
3	Terms and definitions .....	8
4	Deviations from requirements .....	10
5	Proof of the endurable longitudinal compressive force .....	10
5.1	Assessment of endurable longitudinal compressive force .....	10
5.2	Required endurable longitudinal compressive force for use in conventional trains 10 5.3 Assessment of endurable longitudinal compressive force for use in high-capacity trains	11
5.4	Assessment of endurable longitudinal compressive force for vehicles equipped with centre couplers .....	11
5.5	Special vehicle layout .....	11
5.5.1	Permanently coupled units consisting of 2-axle wagons with standard ends or diagonal buffers .....	11
5.5.2	Permanently coupled units with bar couplers .....	12
Annex A (normative) Symbols .....		13
Annex B (normative) Conditions for the execution and evaluation of propelling tests for the determination of the endurable longitudinal compressive force of vehicles with side buffers .....		14
B.1	Test track .....	14
B.2	Test train .....	14
B.2.1	Standard configuration .....	14
B.2.2	Supplementary configuration for 2-axle vehicles with LoB 15,75 m .....	16
B.3	Execution of the tests .....	16
B.4	Measured values .....	17
B.4.1	Measurements during the tests .....	17
B.4.2	Other measurements .....	18
B.5	Used criteria for the evaluation of the endurable longitudinal compressive force .....	18
B.6	Analysis .....	18
B.7	Documentation of results .....	19
B.7.1	General .....	19
B.7.2	Characteristics of the track on which the tests were carried out .....	20
B.7.3	Characteristics of the test vehicle .....	20
B.7.4	Test results .....	20
Annex C (informative) Vehicles incorporated in conventional trains: Conditions for dispensation from the assessment of running safety under longitudinal compressive force .....		21
C.1	General .....	21

C.2	2-axle wagons .....	21
C.3	Wagons with two 2-axle bogies .....	23
C.4	Wagons with 3-axle bogies .....	26
C.5	Railbound construction and maintenance machines .....	27
Annex D	(informative) Conventional trains: Design characteristics of standardized interfaces of permanent coupled units for dispensation from the assessment of running safety under longitudinal compressive force - Specification of interface with diagonal buffers .....	29
Annex E	(informative) Requirements for the use of simulations as proof for endurable longitudinal compressive force .....	30
E.1	Introduction .....	30
E.2	State of the art for the heavy rail system in ENs related to running dynamics .....	30
E.3	Modelling for simulations .....	30
E.3.1	General .....	30
E.3.2	Intermediate wagons and trailing flanking wagon .....	31
E.3.3	Leading flanking wagon .....	32
E.3.4	Test track .....	32
E.4	Validation of the model .....	32
E.5	Performance of simulations .....	33
E.5.1	Required parameters (friction, track, speed etc) .....	33
E.5.2	Criteria applied for evaluation .....	33
Annex F	(informative) Scenarios for the assessment of endurable longitudinal compressive force of a vehicle incorporated in a high-capacity train .....	34
Annex G	(informative) Vehicle incorporated in a high-capacity trains: conditions for dispensation from the assessment of running safety under longitudinal compressive force .....	36
G.1	Introduction .....	36
G.2	Wagons with 2 bogies .....	36
G.3	Articulated wagons with 3 bogies .....	37
Annex H	(informative) Vehicles with centre couplers .....	38
Bibliography	.....	39