

# DIN EN 13715:2006-05 (E)

## Railway applications - Wheelsets and bogies - Wheels - Tread profile

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Definition of the tread profile .....</b>	<b>4</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>6</b>
<b>4.1</b>	<b>Definition of the profiles .....</b>	<b>7</b>
<b>5</b>	<b>Construction method .....</b>	<b>7</b>
<b>5.1</b>	<b>Definition of the axes .....</b>	<b>7</b>
<b>5.2</b>	<b>Base profile .....</b>	<b>7</b>
<b>5.3</b>	<b>Profile construction .....</b>	<b>7</b>
<b>5.3.1</b>	<b>Profile zone H2 - D1 (flange) .....</b>	<b>7</b>
<b>5.3.2</b>	<b>Profile connection zone D1 - C1 .....</b>	<b>8</b>
<b>5.3.3</b>	<b>Profile zone D1 - C1 -D0 for flange thicknesses 28,5 mm e 32,5 mm .....</b>	<b>9</b>
<b>5.3.4</b>	<b>Zone D0 - B1 (B1a or B1b) .....</b>	<b>10</b>
<b>5.3.5</b>	<b>Reverse slope and chamfer .....</b>	<b>11</b>
<b>6</b>	<b>Geometric characteristics .....</b>	<b>11</b>
<b>6.1</b>	<b>R20,5 connecting radius .....</b>	<b>11</b>
<b>6.2</b>	<b>RE and RI 12 mm connecting radii .....</b>	<b>11</b>
<b>6.3</b>	<b>Rfa connecting radius .....</b>	<b>12</b>
<b>6.4</b>	<b>R13 connecting radius .....</b>	<b>12</b>
<b>6.5</b>	<b>Wheel tread .....</b>	<b>12</b>
<b>6.6</b>	<b>Reverse slope - Chamfer .....</b>	<b>12</b>
<b>7</b>	<b>Profile designation .....</b>	<b>12</b>
<b>8</b>	<b>Reference equipment for verification of the wheel profile .....</b>	<b>12</b>
<b>Annex A (normative) Flange .....</b>		<b>13</b>
<b>A.1</b>	<b>Definition of the flange .....</b>	<b>13</b>
<b>A.2</b>	<b>Flange geometry .....</b>	<b>14</b>
<b>Annex B (normative) 1/40th profile .....</b>		<b>15</b>
<b>B.1</b>	<b>Complete reference profile: construction with a 32,5 mm thick flange and 15 % reverse slope .....</b>	<b>15</b>
<b>B.2</b>	<b>Profile construction: specific zones .....</b>	<b>15</b>
<b>Annex C (normative) S1002 profile .....</b>		<b>17</b>
<b>C.1</b>	<b>Complete reference profile: construction with 32,5 mm thick flange and 6,7 % reverse slope .....</b>	<b>17</b>
<b>C.2</b>	<b>Profile construction: specific zones .....</b>	<b>17</b>

<b>Annex D (normative) EPS profile .....</b>	<b>21</b>
<b>D.1 Complete reference profile: construction with 32,5 mm thick flange and 10 % reverse slope .....</b>	<b>21</b>
<b>D.2 Profile construction: specific zones .....</b>	<b>21</b>
<b>Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 96/48/EC .....</b>	<b>24</b>
<b>Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2001/16/EC .....</b>	<b>26</b>
<b>Bibliography .....</b>	<b>28</b>