

DIN EN 13803-2:2008-04 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1435 mm and wider - Part 2: Switches and crossings and comparable alignment design situations with abrupt changes of curvature (includes Corrigendum AC:2007)

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	6
5	General requirements	7
6	Principles for the assessment of abrupt changes of cant deficiency at abrupt changes in curvature	8
6.1	General	8
6.2	Principle based on limiting values of abrupt change of cant deficiency (I)	8
7	Circular curves without transition curves	8
7.1	Limiting values based on the principle of abrupt change of cant deficiency l_{lim}	8
7.1.1	General	8
7.1.2	Switch and crossing layouts	9
7.1.3	Plain line	10
7.2	Limiting values based on the principle of the virtual transition	10
7.3	Minimum radius of horizontal curves	10
8	Combinations of horizontal curves	10
8.1	General	10
8.2	Limiting length of intermediate element(s) between two abrupt changes of curvature (L_{slim})	11
8.3	Abrupt change of cant deficiency (I) at abrupt changes in curvature in combined curves ..	12
8.3.1	Length of intermediate element(s) equal to, or greater than the limiting minimum value ($L_s \geq L_{slim}$)	12
8.3.2	Intermediate element(s) of sub-standard length ($L_s < L_{slim}$) or no intermediate element ($L_s = 0$)	12
8.4	Requirements for preventing buffer locking	13
9	Alignment rules and parameters for designing switch and crossing layouts	14
9.1	General rules	14
9.1.1	Horizontal alignment	14
9.1.2	Vertical alignment	14
9.2	Switch and crossing layouts in straight track without cant	15
9.2.1	Simple turnout	15
9.2.2	Turnouts with variable curvature	15
9.3	Switch and crossing layouts installed on horizontal curves	18
9.3.1	General rules	18
9.3.2	Horizontal radii	18
9.3.3	Cant D	19
9.3.4	Cant deficiency I	19
9.3.5	Cant excess E	20

Annex A (informative) General design considerations	21
Annex B (informative) The installation of switch and crossing layouts	22
B.1 Standard switch and crossing units	22
B.2 Lateral track resistance at the switch panel	22
B.3 Stress transition zone between continuously welded track and jointed track	22
B.4 Switch and crossing layouts on, or near under-bridges	23
B.5 Limits for diamond crossings, diamond crossings with slips and tandem turnouts	23
B.6 Switch and crossing layouts with steel bearers	23
B.7 Abutting turnouts	23
B.8 Crossovers and follow-on turnouts with reverse curves	23
B.9 Scissors crossovers and single or double junctions	24
B.10 Tracks with cant gradients	24
B.11 Influence of cant on the deflection angle in the horizontal plane	24
Annex C (normative) Rules for converting parameter values for track gauges wider than 1 435 mm	26
C.1 Scope	26
C.2 Symbols and abbreviations	26
C.3 Basic hypothesis	26
C.4 Conversion rules	27
C.4.1 Application of I limiting values	27
C.4.2 Cant	27
C.4.3 Equilibrium cant	28
C.4.4 Other formulas and values of the standard	28
C.4.5 Annexes	29
Annex D (informative) Limits of lateral acceleration	30
D.1 Introduction	30
D.2 Wheel-base effect	31
D.3 Limiting values of the non-compensated lateral acceleration	31
D.4 Conclusion	32
Annex E (informative) The principle of virtual transition	33
E.1 Virtual transition at an abrupt change of curvature	33
E.2 Virtual transition at a short intermediate length between two abrupt changes of curvature	33
E.3 Limiting values based on the principle of the virtual transition	34
E.3.1 General	34
E.3.2 Characteristic vehicle with a distance of 20 m between bogie centres	34
E.3.3 Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres	35
Annex F (informative) A method for calculating the maximum permissible speed at the toe of a non-tangential switch	36
Annex G (informative) Constraints and risks associated with the use of maximum (or minimum) limiting values	38
Annex H (informative) The maximum permissible speed of tilting body trains over switch and crossing layouts	39
H.1 General	39
H.2 The maximum permissible speeds over abrupt changes of curvature	39
H.3 The permissible speeds over switch and crossing layouts on curves	39
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 96/48/EC of 23 July 1996 on the interoperability of the trans-European high-speed rail system amended by the EU Directive 2004/50/EC of 29 April 2004	40
Bibliography	41