

# DIN EN 13803-2:2008-04 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1435 mm and wider - Part 2: Switches and crossings and comparable alignment design situations with abrupt changes of curvature (includes Corrigendum AC:2007)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>6</b>
<b>5</b>	<b>General requirements .....</b>	<b>7</b>
<b>6</b>	<b>Principles for the assessment of abrupt changes of cant deficiency at abrupt changes in curvature .....</b>	<b>8</b>
<b>6.1</b>	<b>General .....</b>	<b>8</b>
<b>6.2</b>	<b>Principle based on limiting values of abrupt change of cant deficiency (I) .....</b>	<b>8</b>
<b>7</b>	<b>Circular curves without transition curves .....</b>	<b>8</b>
<b>7.1</b>	<b>Limiting values based on the principle of abrupt change of cant deficiency <math>l_{lim}</math> .....</b>	<b>8</b>
<b>7.1.1</b>	<b>General .....</b>	<b>8</b>
<b>7.1.2</b>	<b>Switch and crossing layouts .....</b>	<b>9</b>
<b>7.1.3</b>	<b>Plain line .....</b>	<b>10</b>
<b>7.2</b>	<b>Limiting values based on the principle of the virtual transition .....</b>	<b>10</b>
<b>7.3</b>	<b>Minimum radius of horizontal curves .....</b>	<b>10</b>
<b>8</b>	<b>Combinations of horizontal curves .....</b>	<b>10</b>
<b>8.1</b>	<b>General .....</b>	<b>10</b>
<b>8.2</b>	<b>Limiting length of intermediate element(s) between two abrupt changes of curvature (<math>L_{slim}</math>) .....</b>	<b>11</b>
<b>8.3</b>	<b>Abrupt change of cant deficiency (I) at abrupt changes in curvature in combined curves ..</b>	<b>12</b>
<b>8.3.1</b>	<b>Length of intermediate element(s) equal to, or greater than the limiting minimum value (<math>L_s \geq L_{slim}</math>) .....</b>	<b>12</b>
<b>8.3.2</b>	<b>Intermediate element(s) of sub-standard length (<math>L_s &lt; L_{slim}</math>) or no intermediate element (<math>L_s = 0</math>) .....</b>	<b>12</b>
<b>8.4</b>	<b>Requirements for preventing buffer locking .....</b>	<b>13</b>
<b>9</b>	<b>Alignment rules and parameters for designing switch and crossing layouts .....</b>	<b>14</b>
<b>9.1</b>	<b>General rules .....</b>	<b>14</b>
<b>9.1.1</b>	<b>Horizontal alignment .....</b>	<b>14</b>
<b>9.1.2</b>	<b>Vertical alignment .....</b>	<b>14</b>
<b>9.2</b>	<b>Switch and crossing layouts in straight track without cant .....</b>	<b>15</b>
<b>9.2.1</b>	<b>Simple turnout .....</b>	<b>15</b>
<b>9.2.2</b>	<b>Turnouts with variable curvature .....</b>	<b>15</b>
<b>9.3</b>	<b>Switch and crossing layouts installed on horizontal curves .....</b>	<b>18</b>
<b>9.3.1</b>	<b>General rules .....</b>	<b>18</b>
<b>9.3.2</b>	<b>Horizontal radii .....</b>	<b>18</b>
<b>9.3.3</b>	<b>Cant D .....</b>	<b>19</b>
<b>9.3.4</b>	<b>Cant deficiency I .....</b>	<b>19</b>
<b>9.3.5</b>	<b>Cant excess E .....</b>	<b>20</b>

Annex A (informative) General design considerations .....	21
Annex B (informative) The installation of switch and crossing layouts .....	22
B.1 Standard switch and crossing units .....	22
B.2 Lateral track resistance at the switch panel .....	22
B.3 Stress transition zone between continuously welded track and jointed track .....	22
B.4 Switch and crossing layouts on, or near under-bridges .....	23
B.5 Limits for diamond crossings, diamond crossings with slips and tandem turnouts .....	23
B.6 Switch and crossing layouts with steel bearers .....	23
B.7 Abutting turnouts .....	23
B.8 Crossovers and follow-on turnouts with reverse curves .....	23
B.9 Scissors crossovers and single or double junctions .....	24
B.10 Tracks with cant gradients .....	24
B.11 Influence of cant on the deflection angle in the horizontal plane .....	24
Annex C (normative) Rules for converting parameter values for track gauges wider than 1 435 mm	26
C.1 Scope .....	26
C.2 Symbols and abbreviations .....	26
C.3 Basic hypothesis .....	26
C.4 Conversion rules .....	27
C.4.1 Application of I limiting values .....	27
C.4.2 Cant .....	27
C.4.3 Equilibrium cant .....	28
C.4.4 Other formulas and values of the standard .....	28
C.4.5 Annexes .....	29
Annex D (informative) Limits of lateral acceleration .....	30
D.1 Introduction .....	30
D.2 Wheel-base effect .....	31
D.3 Limiting values of the non-compensated lateral acceleration .....	31
D.4 Conclusion .....	32
Annex E (informative) The principle of virtual transition .....	33
E.1 Virtual transition at an abrupt change of curvature .....	33
E.2 Virtual transition at a short intermediate length between two abrupt changes of curvature .....	33
E.3 Limiting values based on the principle of the virtual transition .....	34
E.3.1 General .....	34
E.3.2 Characteristic vehicle with a distance of 20 m between bogie centres .....	34
E.3.3 Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres .....	35
Annex F (informative) A method for calculating the maximum permissible speed at the toe of a non-tangential switch .....	36
Annex G (informative) Constraints and risks associated with the use of maximum (or minimum) limiting values .....	38
Annex H (informative) The maximum permissible speed of tilting body trains over switch and crossing layouts .....	39
H.1 General .....	39
H.2 The maximum permissible speeds over abrupt changes of curvature .....	39
H.3 The permissible speeds over switch and crossing layouts on curves .....	39
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 96/48/EC of 23 July 1996 on the interoperability of the trans-European high-speed rail system amended by the EU Directive 2004/50/EC of 29 April 2004 .....	40
Bibliography .....	41