DIN EN 15049:2007-12 (E)

Railway applications - Suspension components - Torsion bar, steel

Contents

Page

Foreword 5

Introduction 6

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Symbols and abbreviations 8

5 Requirements 9
5.1 Introduction 9
5.2 Documents to be provided by the customer 9
5.3 Documents to be provided by the supplier 10
5.4 Design analysis 10
5.5 Arrangement and design 10
5.6 Straight torsion bar ends and connections 12
5.6.1 General 12
5.6.2 Design of the straight torsion bar end 12

6 Product definition 13
6.1 Geometrical characteristics and space envelope 13
6.2 Mechanical requirements 13
6.2.1 Loading and allowable stresses 13
6.2.2 Service life 13
6.2.3 Investigation of the strain 13
6.2.4 Evaluation of the strain 14
6.3 Physical requirements 14
6.3.1 Material grade 14
6.3.2 Internal integrity 14
6.3.3 Inclusion cleanliness 14
6.3.4 Forged torsion bar ends 14
6.3.5 Decarburization 15
6.3.6 Surface condition 15
6.3.7 Residual compressive stresses on the surface 15
6.3.8 Grain size 16
6.4 Surface protection 16
6.4.1 Generalities 16
6.4.2 Temporary protection 16
6.4.3 Permanent protection 16
6.5 Characteristic moment of torsion / angular displacement 17
6.6 Mass 18

7 Mechanical properties for manufacturing 18
7.1 Hardness 18
7.2 Tensile strength 18
7.3 Toughness 18

8 Tests and test procedures 19
8.1 General requirements 19

8.2 Measuring equipment 19
8.3 Tensile strength 19
8.4 Toughness 19
8.5 Hardness 19
8.6 Material 19
8.7 Depth of decarburization 20
8.8 Grain size 20
8.9 Forged torsion bar ends 20
8.10 Residual compressive stresses on the surface 20
8.11 Surface defects 20
8.12 Surface condition 20
8.13 Dimensional check 21
8.14 Characteristic moment of torsion / angular displacement 21
8.15 Mass 21
8.16 Internal integrity 21
8.17 Surface protection 21
8.18 Loading and allowable stresses 21

9 Quality assurance and final approval 22
9.1 Quality assurance system and staff qualification 22
9.2 Product qualification procedures and samples 22
9.3 Control and monitoring of production quality 23
9.3.1 General 23
9.3.2 Quality assurance plan 23
9.3.3 Control by sampling lots 23
9.4 Requirements for control and monitoring of production quality 24
9.4.1 General 24
9.4.2 Non-compliance 26
9.4.3 Documentation 26
9.5 Handling instructions 26

10 Marking of torsion bars 26

11 Packaging 27

Annex A (normative) Material for hot formed and quenched and tempered torsion bars 28

A.1 General 28
A.2 Material for torsion bars, steel 28

Annex B (normative) Inspection of torsion bars made of round bars by the magnetic crack detection method 30

B.1 Object 30
B.2 Tests 30
B.3 Safety measures 30

Annex C (normative) Checking shot peening efficiency by ALMEN method 31

C.1 Field of application 31
C.2 Checking the procedure 31
C.3 Equipment and installations 31
C.3.1 ALMEN A2 test piece 31
C.3.2 Test piece holder 32
C.3.3 ALMEN measuring device 33

Annex D (normative) Examination for inclusions 34

D.1 Object 34
D.2 Test methods 34
D.2.1 Test method according to DIN 50602 34
D.2.2 Test method according to NF A 04-106 35

D.2.3 Test method according to SS 111116 35

Annex E (normative) Taking of test pieces - Areas of the location of test pieces 36

Bibliography 38

Figures Figure 1 -- Example for a straight torsion bar with mounted levers 11

Figure 2 -- Example for a bended torsion bar 11

Figure 3 -- Cylindrical or conical tooth system 12

Figure 4 -- Frictional shrink fit 12

Figure 5 -- Example of the distribution of stresses produced by shot peening as a function of depth 16

Figure 6 -- Torsion bar diagram 17

Figure C.1 -- ALMEN test arrangements 32

Figure C.2 -- ALMEN measuring sytem 33

Figure E.1 -- Area "e" with constant diameter of the torsion bar to take test pieces 36

Figure E.2 -- Location of the test pieces for the tensile strength test 36

Figure E.3 -- Location of the test pieces for the notch impact test 37

Tables Table 1 -- Symbols and definitions 8

Table 2 -- Elements to be defined in the technical specification and agreed by the parties 10

Table 3 -- Checks and tests to be carried out 24

Table 4 -- Test pieces for statistical tests, number of tests 25

Table A.1 -- Guidance values for the maximum mechanical properties of quenched and tempered test pieces 29

Table D.1 -- Degree of cleanliness under the microscope according to DIN 50602 (procedure K), valid for non metallic oxide inclusions 34

Table D.2 -- Acceptable number of fields (small series and wide series) of each type 35

Table D.3 -- Degree of cleanliness by microscopic examination according to SS 111116 (maximum values) 35