ISO 529:1993-01 (E)

Short machine taps and hand taps

Contents

Page

Section 1 General 1
1.1 Scope 1
1.2 Normative references 1

Section 2 ISO metric threads 3
2.1 Threads up to M25 3
2.1.1 Full-diameter shank taps with plain connecting portion 3
2.1.2 Full-diameter shank taps with recess 4
2.1.3 Relieved-shank taps 5
2.2 Threads above M25 7
2.2.1 Relieved-shank taps for coarse pitch metric thread 7
2.2.2 Relieved-shank taps for fine pitch metric thread 8

Section 3 ISO inch threads, "Unified coarse" (UNC) and "Unified fine" (UNF) series 11
3.1 "Unified" series threads up to 25,4 mm 11
3.1.1 Full-diameter shank taps with plain connecting portion 11
3.1.2 Full-diameter shank taps with recess 12
3.1.3 Relieved-shank taps 13
3.2 "Unified" series threads above 25,4 mm 14
3.2.1 Relieved-shank taps for "Unified coarse" series threads 14
3.2.2 Relieved-shank taps for "Unified fine" series threads 15

Section 4 Non-recommended inch threads 16
4.1 "British Standard Whitworth" (BSW) and "British Standard Fine" (BSF) threads 16
4.1.1 Full-diameter shank taps with recess 16
4.1.2 Relieved-shank taps 17
4.2 "British Association" (BA) threads 19
4.2.1 Full-diameter shank taps with plain connecting portion 19
4.2.2 Full-diameter shank taps with recess 20
4.2.3 Relieved-shank taps 21

Annexes

A Shank diameter, overall length and thread length as a function of range of diameters and pitches 22

B Shank diameters and size of driving squares (Extract from ISO 237) 24

C Bibliography 25