

ISO 5608:2012-08 (E)

Turning and copying tool holders and cartridges for indexable inserts - Designation

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Explanation of the designation code | 1 |
| 2.1 | General | 1 |
| 2.2 | Letter and number symbols comprising the designation code | 1 |
| 3 | Compulsory symbols | 2 |
| 3.1 | Symbol for the holding method of the horizontally mounted insert -- Reference position (1) | 2 |
| 3.2 | Symbol for insert shape -- Reference position (2) | 2 |
| 3.3 | Symbol for tool style -- Reference position (3) | 3 |
| 3.4 | Symbol for the insert normal clearance -- Reference position (4) | 5 |
| 3.5 | Symbol for hand of tool -- Reference position 5 | 5 |
| 3.6 | Symbol for tool height -- Reference position (6) | 5 |
| 3.7 | Symbol for tool width -- Reference position (7) | 6 |
| 3.8 | Symbol for tool length -- Reference position (8) | 6 |
| 3.9 | Symbol for indexable insert size -- Reference position (9) | 8 |
| 4 | Optional symbol: symbol for special tolerances -- Reference position (10) | 8 |
| Annex A (informative) Relationship between designations in this International Standard and the ISO 13399 series | | 10 |
| Bibliography | | 11 |