ISO/TS 13399-308:2016-02 (E)

Cutting tool data representation and exchange - Part 308: Creation and exchange of 3D models - Milling cutters with arbor hole for indexable inserts

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Starting elements, coordinate systems, planes 2
3.1 General 2
3.2 Reference system 2
3.3 Coordinate system at the cutting part 3
3.4 Planes 3
3.5 Design of the pocket seat and cutting reference point (CRP) of the insert 4
3.6 Adjustment coordinate system on workpiece side 7
3.6.1 General 7
3.6.2 Designation of the coordinate system workpiece side 8

4 Design of the model 9
4.1 General 9
4.2 Necessary parameters for the connection interface feature 10
4.3 Necessary properties for inserts 10
4.3.1 General 10
4.3.2 Properties for equilateral, equiangular and equilateral, nonequiangular inserts10 4.3.3 Properties for nonequilateral, equiangular and nonequilateral, nonequiangular inserts 11
4.3.4 Design of the pocket seat feature 12

5 Face milling cutter 12
5.1 General 12
5.2 Necessary properties 13
5.3 Basic geometry 13
5.4 Determination of the position of the mounting coordinate system of insert 14
5.5 Chip flute and pocket seat 15
5.6 Face milling cutter, assembly 16

6 Shoulder milling cutter 17
6.1 General 17
6.2 Necessary properties 17
6.3 Basic geometry 17
6.4 Determination of the position of the mounting coordinate system of insert 17
6.5 Chip flute and pocket seat 18
6.6 Shoulder milling cutter, assembly 18

7 Plain milling cutter 19
7.1 General 19
7.2 Necessary properties 19
7.3 Basic geometry 20
7.4 Determination of the position of the mounting coordinate system of insert 20
7.5 Chip flute and pocket seat 21
7.6 Plain milling cutter, assembly 23

8 Shell milling cutter 23
8.1 General 23
8.2 Necessary properties 24
8.3 Basic geometry 24
8.4 Determination of the position of the mounting coordinate system of insert 25
8.5 Chip flute and pocket seat 25
8.6 Shell milling cutter, assembly 25

9 Full-side-slot milling cutter 25
9.1 General 25
9.2 Necessary properties 26
9.3 Basic geometry 26
9.4 Determination of the position of the mounting coordinate system of insert 27
9.5 Chip flute and pocket seat 28
9.6 Assembly of a full-side slot milling cutter 30

10 Half-side slot milling cutter 31
10.1 General 31
10.2 Necessary properties 31
10.3 Basic geometry 31
10.4 Determination of the position of the mounting coordinate system of insert 31
10.5 Chip flute and pocket seat 32
10.6 Half-side slot milling cutter, assembly 32

11 Full-sideprofileslotmillingcutter 33
11.1 General 33
11.2 Necessary properties 33
11.3 Basic geometry 34
11.4 Determination of the position of the mounting coordinate system of insert 34
11.5 Chip flute and pocket seat 34
11.6 Full-side profile slot milling cutter, assembly 34

12 Full-side angular slot milling cutter 35
12.1 General 35
12.2 Necessary properties 35
12.3 Basic geometry 36
12.4 Determination of the position of the mounting coordinate system of insert 36
12.5 Chip flute and pocket seat 36
12.6 Full-side angular slot milling cutter, assembly 36

13 Saw blade/slitting cutter 36
13.1 General 36
13.2 Necessary properties 37
13.3 Basic geometry 37
13.4 Determination of the position of the mounting coordinate system of insert 38
13.5 Chip flute and pocket seat 40
13.6 Saw blade/slitting cutter, assembly 41

14 Design of details 42
14.1 Basics for modelling 42
14.2 Fixing threads for inserts 42
14.3 Contact surfaces/drive keys -- Orientation 42
14.4 Chamfers, roundings, others 42

15 Attributes of surfaces -- Visualization of the model features 42

16 Structure of the design elements (tree of model) 42

17 Data exchange model 43

Annex A (informative) Information about nominal dimensions 45

Bibliography 46