

ISO 22917:2016-02 (E)

Precision superabrasives - Limit deviations and run-out tolerances for grinding wheels with diamond or cubic boron nitride

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Limit deviations and run-out tolerance abbreviations | 2 |
| 5 | Straight, recessed, tapered and hubbed grinding wheels | 3 |
| 5.1 | Grinding wheels for peripheral grinding | 3 |
| 5.1.1 | Designations | 3 |
| 5.1.2 | Limit deviations and run-out tolerances for grinding wheels for peripheral grinding | 4 |
| 5.2 | Grinding wheels for face grinding | 8 |
| 5.2.1 | Designations | 8 |
| 5.2.2 | Limit deviations and run-out tolerances for grinding wheels for face grinding | 10 |
| 6 | Mounted points | 13 |
| 6.1 | Designation | 13 |
| 6.2 | Limit deviations and circular run-out tolerances | 14 |
| 6.2.1 | Limit deviations of the outside diameter, TD, of the thickness, TT, of the depth of superabrasive section, TX, and circular run-out tolerance, axial, TRL | 14 |
| 6.2.2 | Limit deviations of the spindle diameter, TSd, and of the reduced diameter of spindle, TS1 | 14 |
| 6.2.3 | Limit deviations of the overall length, TL, and of the reduced length of spindle, TL4 | 14 |
| 7 | Superabrasives with metal core for hand-held grinding | 15 |
| 7.1 | Designation | 15 |
| 7.2 | Limit deviations and run-out tolerances | 15 |
| 7.2.1 | Limit deviations of the outside diameter, TD, of the overall thickness, TT, circular run-out tolerance, axial, TPL, and circular run-out tolerance, radial, TRL | 15 |
| 7.2.2 | Limit deviations of the bore diameter, TH | 15 |
| 7.2.3 | Limit deviations of the depth of superabrasive section, TX | 16 |
| 7.2.4 | Limit deviations of the rim width, TW | 16 |
| 7.2.5 | Limit deviations of the thickness at bore, TE | 16 |
| 7.2.6 | Limit deviations of the contact surface diameter, TJ, and of the recess diameter, TK | 17 |