ISO/TS 13399-307:2016-02 (E)

Cutting tool data representation and exchange - Part 307: Creation and exchange of 3D models - End mills for indexable inserts

Contents

Page

Foreword vi

Introduction viii

1 Scope 1

2 Normative references 1

3 Starting elements, coordinate systems, planes 2
3.1 General 2
3.2 Reference system 2
3.3 Coordinate system at the cutting part 3
3.4 Planes 4
3.5 Design of the pocket seat and cutting reference point (CRP) of the insert 5
3.6 Adjustment coordinate system on workpiece side 8
3.6.1 General 8
3.6.2 Designation of the coordinate system workpiece side 8

4 Design of the model 9
4.1 General 9
4.2 Necessary parameters for the connection interface feature 9
4.3 Necessary properties for inserts 10
4.3.1 General 10
4.3.2 Properties for equilateral, equiangular and equilateral, non- equiangular inserts 10
4.3.3 Properties for non-equilateral, equiangular and non-equilateral, non- equiangular inserts 11
4.3.4 Design of the pocket seat feature 11

5 End mill, non-centre cutting, single row 11
5.1 General 11
5.2 Necessary properties 12
5.3 Basic geometry 13
5.4 Determination of the position of the mounting coordinate system of insert 13
5.5 Chip flute and pocket seat 14
5.6 Assembly of a single row, non-centre cutting end mill 15

6 Single row, non-centre cutting V-groove end mill 16
6.1 General 16
6.2 Necessary properties 17
6.3 Basic geometry 17
6.4 Determination of the position of the mounting coordinate system of insert 17
6.5 Chip flute and pocket seat 18
6.6 Single row, non-centre cutting V-groove end mill assembly 19

7 Single row, non-centre-cutting dovetail end mill 20
7.1 General 20
7.2 Necessary properties 20
7.3 Basic geometry 21
7.4 Determination of the position of the mounting coordinate system of insert 21
7.5 Chip flute and pocket seat 21
7.6 Single row, non-centre-cutting dovetail end mill assembly 22

8 T-slot end mill 22
8.1 General 22
8.2 Necessary properties 23
8.3 Basic geometry 23
8.4 Determination of the position of the mounting coordinate system of insert 23
8.5 Chip flute and pocket seat 24
8.6 Assembly of a T-slot end mill 25

9 Single row, rounded end mill 26
9.1 General 26
9.2 Necessary properties 27
9.3 Basic geometry 27
9.4 Determination of the position of the mounting coordinate system of insert 28
9.5 Chip flute and pocket seat 28
9.6 Assembly of a rounded end mill 30

10 Threading end mill 30
10.1 General 30
10.2 Necessary properties 31
10.3 Basic geometry 32
10.4 Determination of the position of the mounting coordinate system of insert 32
10.5 Chip flute and pocket seat 33
10.6 Assembled threading end mill 34

11 End mill, non-centre-cutting, multiple rows 35
11.1 General 35
11.2 Necessary properties 35
11.3 Basic geometry 36
11.4 Determination of the position of the mounting coordinate system of insert 36
11.5 Chip flute and pocket seat 38
11.6 Multiple rows, non-centre-cutting end mill assembly 39

12 Angular end mill, non-centre-cutting, multiple rows 40
12.1 General 40
12.2 Necessary properties 40
12.3 Basic geometry 41
12.4 Determination of the position of the mounting coordinate system of insert 41
12.5 Chip flute and pocket seat 41
12.6 Multiple rows non-centre-cutting angular end mill assembly 42

13 End mill, centre-cutting, multiple rows 42
13.1 General 42
13.2 Necessary properties 43
13.3 Basic geometry 43
13.4 Determination of the position of the mounting coordinate system of insert 43
13.5 Chip flute and pocket seat 44
13.6 Multiple rows, centre-cutting angular end mill assembly 45

14 Spot-facing end mill 46
14.1 General 46
14.2 Necessary properties 46
14.3 Basic geometry 47
14.4 Determination of the position of the mounting coordinate system of insert 47
14.5 Chip flute and pocket seat 47
14.6 Assembled spot-facing end mill 49

15 Straight ball-nosed end mill 49
15.1 General 49
15.2 Necessary properties 50
15.3 Basic geometry 50
15.4 Determination of the position of the mounting coordinate system of insert 51

15.5 Chip flute and pocket seat 52
15.6 Straight ball-nosed end mill assembly 53

16 Angular ball-nosed end mill 53
16.1 General 53
16.2 Necessary properties 54
16.3 Basic geometry 54
16.4 Determination of the position of the mounting coordinate system of insert 54
16.5 Chip flute and pocket seat 54
16.6 Angular ball-nosed end mill assembly 54

17 Die and mould end mill 54
17.1 General 54
17.2 Necessary properties 55
17.3 Basic geometry 56
17.4 Determination of the position of the mounting coordinate system of insert 56
17.5 Chip flute and pocket seat 56
17.6 Die end mill assembly 58

18 Bell-style end mill 58
18.1 General 58
18.2 Necessary properties 59
18.3 Basic geometry 60
18.4 Determination of the position of the mounting coordinate system of insert 60
18.5 Chip flute and pocket seat 61
18.6 Bell-style end mill assembly 61

19 Design of details 61
19.1 Basis for modelling 61
19.2 Fixing threads for inserts 62
19.3 Contact/clamping surfaces -- Orientation 62
19.4 Chamfers and roundings 62

20 Attributes of surfaces -- Visualization of the model features 62

21 Structure of the design elements (tree of model) 62

22 Data exchange model 63

Annex A (informative) Information about nominal dimensions 65

Bibliography 66