

ISO/TS 13399-307:2016-02 (E)

Cutting tool data representation and exchange - Part 307: Creation and exchange of 3D models - End mills for indexable inserts

Contents		Page
Foreword		vi
Introduction		viii
1	Scope	1
2	Normative references	1
3	Starting elements, coordinate systems, planes	2
3.1	General	2
3.2	Reference system	2
3.3	Coordinate system at the cutting part	3
3.4	Planes	4
3.5	Design of the pocket seat and cutting reference point (CRP) of the insert	5
3.6	Adjustment coordinate system on workpiece side	8
3.6.1	General	8
3.6.2	Designation of the coordinate system workpiece side	8
4	Design of the model	9
4.1	General	9
4.2	Necessary parameters for the connection interface feature	9
4.3	Necessary properties for inserts	10
4.3.1	General	10
4.3.2	Properties for equilateral, equiangular and equilateral, non- equiangular inserts	10
4.3.3	Properties for non-equilateral, equiangular and non-equilateral, non- equiangular inserts	11
4.3.4	Design of the pocket seat feature	11
5	End mill, non-centre cutting, single row	11
5.1	General	11
5.2	Necessary properties	12
5.3	Basic geometry	13
5.4	Determination of the position of the mounting coordinate system of insert	13
5.5	Chip flute and pocket seat	14
5.6	Assembly of a single row, non-centre cutting end mill	15
6	Single row, non-centre cutting V-groove end mill	16
6.1	General	16
6.2	Necessary properties	17
6.3	Basic geometry	17
6.4	Determination of the position of the mounting coordinate system of insert	17
6.5	Chip flute and pocket seat	18
6.6	Single row, non-centre cutting V-groove end mill assembly	19
7	Single row, non-centre-cutting dovetail end mill	20
7.1	General	20
7.2	Necessary properties	20
7.3	Basic geometry	21
7.4	Determination of the position of the mounting coordinate system of insert	21
7.5	Chip flute and pocket seat	21
7.6	Single row, non-centre-cutting dovetail end mill assembly	22

8	T-slot end mill	22
8.1	General	22
8.2	Necessary properties	23
8.3	Basic geometry	23
8.4	Determination of the position of the mounting coordinate system of insert	23
8.5	Chip flute and pocket seat	24
8.6	Assembly of a T-slot end mill	25
9	Single row, rounded end mill	26
9.1	General	26
9.2	Necessary properties	27
9.3	Basic geometry	27
9.4	Determination of the position of the mounting coordinate system of insert	28
9.5	Chip flute and pocket seat	28
9.6	Assembly of a rounded end mill	30
10	Threading end mill	30
10.1	General	30
10.2	Necessary properties	31
10.3	Basic geometry	32
10.4	Determination of the position of the mounting coordinate system of insert	32
10.5	Chip flute and pocket seat	33
10.6	Assembled threading end mill	34
11	End mill, non-centre-cutting, multiple rows	35
11.1	General	35
11.2	Necessary properties	35
11.3	Basic geometry	36
11.4	Determination of the position of the mounting coordinate system of insert	36
11.5	Chip flute and pocket seat	38
11.6	Multiple rows, non-centre-cutting end mill assembly	39
12	Angular end mill, non-centre-cutting, multiple rows	40
12.1	General	40
12.2	Necessary properties	40
12.3	Basic geometry	41
12.4	Determination of the position of the mounting coordinate system of insert	41
12.5	Chip flute and pocket seat	41
12.6	Multiple rows non-centre-cutting angular end mill assembly	42
13	End mill, centre-cutting, multiple rows	42
13.1	General	42
13.2	Necessary properties	43
13.3	Basic geometry	43
13.4	Determination of the position of the mounting coordinate system of insert	43
13.5	Chip flute and pocket seat	44
13.6	Multiple rows, centre-cutting angular end mill assembly	45
14	Spot-facing end mill	46
14.1	General	46
14.2	Necessary properties	46
14.3	Basic geometry	47
14.4	Determination of the position of the mounting coordinate system of insert	47
14.5	Chip flute and pocket seat	47
14.6	Assembled spot-facing end mill	49
15	Straight ball-nosed end mill	49
15.1	General	49
15.2	Necessary properties	50
15.3	Basic geometry	50
15.4	Determination of the position of the mounting coordinate system of insert	51

15.5	Chip flute and pocket seat	52
15.6	Straight ball-nosed end mill assembly	53
16	Angular ball-nosed end mill	53
16.1	General	53
16.2	Necessary properties	54
16.3	Basic geometry	54
16.4	Determination of the position of the mounting coordinate system of insert	54
16.5	Chip flute and pocket seat	54
16.6	Angular ball-nosed end mill assembly	54
17	Die and mould end mill	54
17.1	General	54
17.2	Necessary properties	55
17.3	Basic geometry	56
17.4	Determination of the position of the mounting coordinate system of insert	56
17.5	Chip flute and pocket seat	56
17.6	Die end mill assembly	58
18	Bell-style end mill	58
18.1	General	58
18.2	Necessary properties	59
18.3	Basic geometry	60
18.4	Determination of the position of the mounting coordinate system of insert	60
18.5	Chip flute and pocket seat	61
18.6	Bell-style end mill assembly	61
19	Design of details	61
19.1	Basis for modelling	61
19.2	Fixing threads for inserts	62
19.3	Contact/clamping surfaces -- Orientation	62
19.4	Chamfers and roundings	62
20	Attributes of surfaces -- Visualization of the model features	62
21	Structure of the design elements (tree of model)	62
22	Data exchange model	63
	Annex A (informative) Information about nominal dimensions	65
	Bibliography	66