

ISO 1832:2017-02 (E)

Indexable inserts for cutting tools - Designation

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Explanation of designation code	1
5 Symbols	3
5.1 Symbol for insert shape -- Reference	3
5.2 Symbol for normal clearance -- Reference	4
5.3 Symbol for tolerance class -- Reference	4
5.4 Symbol for fixing and/or chip breakers -- Reference	7
5.5 Symbol for insert size -- Reference	9
5.6 Symbol for insert thickness -- Reference	9
5.7 Symbol for insert corner configuration -- Reference	10
6 Optional symbols for indexable inserts	12
6.1 General	12
6.2 Symbol for cutting edge condition -- Reference	12
6.3 Symbol for the corner type and the application of the insert (direction of feed motion) -- Reference	13
7 Additional symbols for tipped inserts	13
7.1 General	13
7.2 Size of cutting edge condition -- Reference	13
7.2.1 General	13
7.2.2 E = rounded	13
7.2.3 T = chamfered	14
7.2.4 S = chamfered and rounded	14
7.2.5 K = double chamfered	15
7.2.6 P = double chamfered and rounded	16
7.3 Style of tipped or solid cutting edge and number of tipped corners -- Reference	16
7.4 Length of tipped cutting edge -- Reference	18
Annex A (informative) Symbols for insert size (reference) according to standardized inscribed circles for equilateral and round inserts	20
Annex B (informative) Symbols for standardized insert thicknesses (reference)	22
Annex C (informative) Relationship between designations in this document and the ISO 13399 series	23
Bibliography	24