ISO/TS 13399-315:2018 (E)

Cutting tool data representation and exchange — Part 315: Creation and exchange of 3D models — Modelling of machine operated feed out tools

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Starting elements, coordinate systems, planes

4.1 General
4.2 Reference system (PCS — Primary coordinate system)
4.3 Coordinate system at the cutting part
4.4 Planes
4.5 Adjustment coordinate system on workpiece side
4.5.1 General
4.5.2 Designation of the coordinate system workpiece side

5 Design of the model

5.1 General
5.2 Necessary parameters for the feed out motion of the slides

6 Machine operated feed out tool with one linear slide for internal machining

6.1 General
6.2 Necessary properties
6.3 Location of coordinate systems
6.4 Assembled feed out tool with one linear slide for internal machining

7 Machine operated feed out tool with one linear slide for external machining

7.1 General
7.2 Necessary properties
7.3 Location of coordinate systems
7.4 Assembled feed out tool with one linear slide for external machining

8 Machine operated feed out tool with two linear slides for internal machining

8.1 General
8.2 Necessary properties
8.3 Location of coordinate systems and assembled feed out tool

9 Machine operated feed out tool with two linear slides for external machining

9.1 General
9.2 Necessary properties
9.3 Location of coordinate systems
9.4 Assembled feed out tool with two linear slides for external machining

10 Machine operated feed out tool with two linear slides for internal pull back machining

10.1 General
10.2 Necessary properties
10.3 Location of coordinate systems and assembled feed out tool

11 Machine operated feed out tool with one linear slide for external pull back machining

11.1 General

11.2 Necessary properties
11.3 Location of coordinate systems and assembled feed out tool

12 Machine operated feed out tool with one inclined slide

12.1 General
12.2 Necessary properties
12.3 Location of coordinate systems and assembled feed out tool

13 Machine operated feed out tool with two inclined slides

13.1 General
13.2 Necessary properties
13.3 Location of coordinate systems
13.4 Assembled feed out tool with two inclined slides for internal machining

14 Machine operated feed out tool with one rotatory slide

14.1 General
14.2 Necessary properties
14.3 Location of coordinate systems
14.4 Assembled feed out tool with one rotary slide

15 Machine operated feed out tool with one swing slide

15.1 General
15.2 Necessary properties
15.3 Location of coordinate systems
15.4 Assembled feed out tool with one swing slide

16 Machine operated feed out tool with one peripheral swivelling slide

16.1 General
16.2 Necessary properties
16.3 Location of coordinate systems
16.4 Assembled feed out tool with one peripheral swivelling slide

17 Machine operated feed out tool with one central swivelling slide

17.1 General
17.2 Necessary properties
17.3 Location of coordinate systems
17.4 Assembled feed out tool with one central swivelling slide

18 Machine operated feed out tool with multiple slides

18.1 General
18.2 Necessary properties
18.3 Location of coordinate systems
18.4 Example of an assembled feed out tool with three slides

19 Components of machine operated feed out tools

19.1 Flange adaptor
19.1.1 General
19.1.2 Necessary properties
19.1.3 Example of a model of a flange adaptor
19.2 Slide
19.2.1 General
19.2.2 Necessary properties
19.2.3 Example of a model of a slide
19.3 Cartridge carrier
19.3.1 General
19.3.2 Necessary properties
19.3.3 Example of a model of a cartridge carrier
19.4 Stator
19.4.1 General
19.4.2 Necessary properties
19.4.3 Example of a model of a stator

20 Design of details

20.1 Basics for modelling

20.2 Fixing threads for inserts
20.3 Contact/clamping surfaces — Orientation
20.4 Chamfers and roundings

21 Data exchange model

Annex A (informative) Information about nominal dimensions

Page count: 40