ISO 13942:2019 (E)

Bonded abrasive products — Limit deviations and run-out tolerances

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 General

6 Straight grinding wheels, recessed, relieved and hubbed wheels

- 6.1 Relevant shape types according to ISO 525
- 6.2 Straight grinding wheels for general applications
- 6.2.1 Limit deviations TD of the outside diameter, axial run-out tolerance TPL and radial run-out tolerances TRL
- 6.2.2 Limit deviations TH of the hole diameter
- 6.2.3 Limit deviations TP of the recess diameter and assignment of radii R
- 6.2.4 Limit deviations TT, TU of grinding wheel thickness dimensions
- 6.2.5 Limit deviations TE of thickness at bore
- 6.3 Straight grinding wheels for other applications not specified in 6.2
- 6.3.1 Examples of application
- 6.3.2 Limit deviations TD of the outside diameter, axial run-out tolerance TPL and radial run-out tolerance TRL
- 6.3.3 Limit deviations TH of the hole diameter
- 6.3.4 Limit deviations TP of the recess diameters and assignment of radii R
- 6.3.5 Limit deviations TT of the grinding wheel thickness
- 6.3.6 Limit deviations TE of thickness at bore
- 6.4 Grinding wheels for high-pressure grinding
- 6.5 Straight grinding wheels used in sets
- 6.5.1 General
- 6.5.2 Limit deviations TD of the outside diameter
- 6.5.3 Limit deviations TT of the grinding wheel thickness
- 6.6 Cemented or clamped cylinder wheels and disc wheels
- 6.6.1 Relevant shape types according to ISO 525
- 6.6.2 Limit deviations TD of the outside diameter, axial run-out tolerance TPL and radial run-out tolerance TRL
- 6.6.3 Limit deviations TH of the hole diameter
- 6.6.4 Limit deviations TW of the wall thickness
- 6.6.5 Limit deviations TD of the outside diameter of grinding wheel sets
- 6.6.6 Limit deviations TT of the grinding wheel thickness

7 Dish and cup wheels

- 7.1 Relevant shape types according to ISO 525
- 7.2 Dish and cup wheels for general applications
- 7.3 Dish and cup wheels for tool and cutter grinding

8 Grinding and cutting-off wheels

- 8.1 Relevant shape types according to ISO 525
- 8.2 Limit deviations TD of the outside diameter, axial run-out tolerance TPL, and the radial run-out tolerance TRL
- 8.3 Limit deviations TH of the hole diameter
- 8.4 Limit deviations TT and TU of the grinding wheel thickness

9 Segments

10 Cones and plugs with threaded insert

11 Honing stones and superfinishing stones

12 Hand finishing sticks

13 Spindle mounted points and wheels

Page count: 27