

DIN ISO 6987:2022-08 (E)

Indexable hard material inserts with rounded corners, with partly cylindrical fixing hole - Dimensions (ISO 6987:2012)

Contents		Page
National foreword		3
National Annex NA (informativ) Bibliography		5
Foreword		6
1	Scope	7
2	Normative references	7
3	Types of inserts	7
4	Interchangeability	8
4.1	Tolerances	8
4.2	Thickness, s, of inserts with chip breakers	8
4.3	Fixing hole	8
5	Designation and marking	9
5.1	Designation	9
5.2	Marking	10
6	Measurement	10
7	Recommended dimensions	10
7.1	Triangular inserts -- TC	10
7.2	Triangular inserts -- TP	11
7.3	Square inserts -- SC	12
7.4	Square inserts -- SP	13
7.5	Rhombic inserts with 80° included angle -- CC	14
7.6	Rhombic inserts with 80° included angle -- CP	15
7.7	Rhombic inserts with 55° included angle -- DC	16
7.8	Rhombic inserts with 35° included angle -- VB and VC	17
7.9	Round inserts -- RC	18
7.10	Round inserts -- RP	18
7.11	Hexagonal (trigon) inserts with 80° included angle -- WC	19
Annex A (normative) Tolerances for d, m, m1, m2 and s -- Extract from ISO 1832		20
Annex B (normative) Methods of measurement of dimension m		22
B.1	Triangular inserts	22
B.2	Square inserts	22
B.3	Rhombic inserts	23
B.4	Round inserts	23
B.5	Hexagonal inserts	24
Annex C (normative) Size ranges		25
Annex D (informative) Relationship between designations in this International Standard and the ISO 13399 series		28
D.1	Relationship between designations	28
Bibliography		29