

DIN 6535:2024-03 (E)

Cylindrical shanks made of hard materials for machining tools - Dimensions

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Dimensions and designation	5
4.1	General	5
4.2	Type HA: Plain cylindrical shank	5
4.3	Type HB: Single-flatted cylindrical shank	5
4.4	Type HE: Cylindrical shank with inclined clamping surface	8
4.5	Type HF: Cylindrical shank with a 90° conical fitting for cooling lubricant supply	10
4.5.1	General	10
4.5.2	Design A with central cooling lubricant supply	10
4.5.3	Design B with decentralized cooling lubricant supply with cooling channel connection ...	10
4.5.4	Design C with decentralized cooling lubricant supply with double cone	11
4.5.5	Dimensions	12
5	Design	12
Bibliography		13

Figures

Figure 1 — Type HA: Plain cylindrical shank.....	5
Figure 2 — Type HB: Single-flatted cylindrical shank ($d_1 = 6$ mm to 20 mm).....	6
Figure 3 — Type HB: Double-flatted cylindrical shank ($d_1 = 25$ mm and 32 mm).....	6
Figure 4 — Type HE: Cylindrical shank with inclined clamping surface ($d_1 = 6$ mm to 20 mm).....	8
Figure 5 — Type HE: Cylindrical shank with inclined clamping surface ($d_1 = 25$ mm and 32 mm).....	9
Figure 6 — Type HF, design A: Central cooling lubricant supply	10
Figure 7 — Type HF, design B: Decentralized cooling lubricant supply with cooling channel connection	11
Figure 8 — Type HF, design C: Decentralized cooling lubricant supply with double cone	11

Tables

Table 1 — Type HA: Plain cylindrical shank, dimensions	5
Table 2 — Type HB: Double-flatted cylindrical shank, dimensions	7
Table 3 — Type HE: Cylindrical shank with inclined clamping surface, dimensions	9
Table 4 — Type HF: Cylindrical shank for MQL, dimensions.....	12