

# ISO 5686-3:2024-10 (E)

## Polygonal turret interface with flat contact surface - Part 3: Coupling for driven tool holders with shanks of type F and A

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Couplings for polygonal taper shanks, dimensions .....</b>	<b>1</b>
<b>4.1</b>	<b>General .....</b>	<b>1</b>
<b>4.2</b>	<b>Coupling for driven tool holders with polygonal taper shank .....</b>	<b>2</b>
<b>4.3</b>	<b>Dimensions .....</b>	<b>2</b>
<b>5</b>	<b>Design .....</b>	<b>3</b>
<b>5.1</b>	<b>Assignment of PTI-couplings to PTI-shanks .....</b>	<b>3</b>
<b>5.2</b>	<b>Low-backlash and backlash-free application .....</b>	<b>3</b>
<b>5.3</b>	<b>Material and heat treatment .....</b>	<b>3</b>
<b>6</b>	<b>Designation .....</b>	<b>3</b>
<b>Annex A (informative) Application of PTI types in turret lathes .....</b>		<b>4</b>
<b>Bibliography .....</b>		<b>6</b>