

# ISO 22917:2004-12 (E)

## Superabrasives - Limit deviations and run-out tolerances for grinding wheels with diamond or cubic boron nitride

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Limit deviations and run-out tolerance abbreviations</b> .....	<b>3</b>
<b>5</b>	<b>Straight, recessed, tapered and hubbed grinding wheels</b> .....	<b>4</b>
<b>5.1</b>	<b>Grinding wheels for peripheral grinding</b> .....	<b>4</b>
<b>5.2</b>	<b>Grinding wheels for face grinding</b> .....	<b>9</b>
<b>6</b>	<b>Mounted points</b> .....	<b>14</b>
<b>6.1</b>	<b>Designation</b> .....	<b>14</b>
<b>6.2</b>	<b>Limit deviations and circular run-out tolerances</b> .....	<b>15</b>
<b>7</b>	<b>Superabrasives with metal core for hand-held grinding</b> .....	<b>16</b>
<b>7.1</b>	<b>Designation</b> .....	<b>16</b>
<b>7.2</b>	<b>Limit deviations and run-out tolerances</b> .....	<b>17</b>