

DIN EN 12680-2:2026-03 (E)

Founding - Ultrasonic testing - Part 2: Steel castings for highly stressed components

| Contents | | Page |
|--|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Requirements | 6 |
| 4.1 | Order information | 6 |
| 4.2 | Extent of testing | 6 |
| 4.3 | Wall section zones | 6 |
| 4.4 | Maximum acceptable size of discontinuities | 6 |
| 4.4.1 | General | 6 |
| 4.4.2 | Indications without measurable dimensions | 6 |
| 4.4.3 | Indications with measurable dimensions | 6 |
| 4.5 | Qualification of personnel | 7 |
| 4.6 | Severity levels | 8 |
| 5 | Testing | 8 |
| 5.1 | Principles | 8 |
| 5.2 | Material | 8 |
| 5.3 | Equipment and coupling medium | 9 |
| 5.3.1 | Ultrasonic instrument | 9 |
| 5.3.2 | Probes | 9 |
| 5.3.3 | Checking of the ultrasonic test equipment | 9 |
| 5.3.4 | Coupling medium | 9 |
| 5.3.5 | Test sensitivity and resolution of detection | 9 |
| 5.4 | Preparation of casting surfaces for testing | 10 |
| 5.5 | Test procedure | 10 |
| 5.5.1 | General | 10 |
| 5.5.2 | Range setting | 10 |
| 5.5.3 | Sensitivity setting | 11 |
| 5.5.4 | Consideration of various types of indications | 11 |
| 5.5.5 | Recording limits | 12 |
| 5.5.6 | Evaluation of discontinuities to be recorded | 12 |
| 5.5.7 | Characterization and sizing of discontinuities | 12 |
| 5.6 | Test report | 13 |
| Annex A (normative) Resolution of detection of the instrument-probe combination | | 21 |
| Annex B (informative) Sound-beam diameters | | 22 |
| Annex C (informative) Types of indications generated by typical discontinuities | | 24 |
| Annex D (informative) Significant technical changes between this document and the previous edition | | 36 |
| Bibliography | | 37 |