DIN EN 12680-2:2026-03 (E)

Founding - Ultrasonic testing - Part 2: Steel castings for highly stressed components

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Requirements 6
4.1 Order information 6
4.2 Extent of testing 6
4.3 Wall section zones 6
4.4 Maximum acceptable size of discontinuities 6
4.4.1 General 6
4.4.2 Indications without measurable dimensions 6
4.4.3 Indications with measurable dimensions 6
4.5 Qualification of personnel 7
4.6 Severity levels 8

5 Testing 8
5.1 Principles 8
5.2 Material 8
5.3 Equipment and coupling medium 9
5.3.1 Ultrasonic instrument 9
5.3.2 Probes 9
5.3.3 Checking of the ultrasonic test equipment 9
5.3.4 Coupling medium 9
5.3.5 Test sensitivity and resolution of detection 9
5.4 Preparation of casting surfaces for testing 10
5.5 Test procedure 10
5.5.1 General 10
5.5.2 Range setting 10
5.5.3 Sensitivity setting 11
5.5.4 Consideration of various types of indications 11
5.5.5 Recording limits 12
5.5.6 Evaluation of discontinuities to be recorded 12
5.5.7 Characterization and sizing of discontinuities 12
5.6 Test report 13

Annex A (normative) Resolution of detection of the instrument-probe combination 21

Annex B (informative) Sound-beam diameters 22

Annex C (informative) Types of indications generated by typical discontinuities 24

Annex D (informative) Significant technical changes between this document and the previous edition 36

Bibliography 37