DIN EN 12680-3:2026-03 (E)

Founding - Ultrasonic testing - Part 3: Spheroidal graphite cast iron castings

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Requirements 5
4.1 Order information 5
4.2 Extent of testing 5
4.3 Wall section zones 5
4.4 Maximum acceptable size of discontinuities 6
4.5 Qualification of personnel 6
4.6 Severity levels 6

5 Testing 6
5.1 Principles 6
5.2 Material 6
5.3 Equipment and coupling medium 6
5.3.1 Ultrasonic instrument 6
5.3.2 Probes 7
5.3.3 Checking of the ultrasonic test equipment 8
5.3.4 Coupling medium 8
5.3.5 Time base range and sensitivity setting of the ultrasonic test equipment 8
5.3.6 Detection sensitivity 9
5.4 Preparation of casting surfaces for testing 9
5.5 Test procedure 9
5.5.1 General 9
5.5.2 Sensitivity setting 9
5.5.3 Consideration of various types of indications 10
5.5.4 Evaluation and recording of indications 10
5.5.5 Assessment of discontinuities to be recorded 10
5.5.6 Characterization and sizing of discontinuities 10
5.6 Test report 11

Annex A (informative) Significant technical changes between this document and the previous edition 21

Bibliography 23