

DIN EN 12680-3:2026-03 (E)

Founding - Ultrasonic testing - Part 3: Spheroidal graphite cast iron castings

Contents		Page
European foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Requirements	5
4.1	Order information	5
4.2	Extent of testing	5
4.3	Wall section zones	5
4.4	Maximum acceptable size of discontinuities	6
4.5	Qualification of personnel	6
4.6	Severity levels	6
5	Testing	6
5.1	Principles	6
5.2	Material	6
5.3	Equipment and coupling medium	6
5.3.1	Ultrasonic instrument	6
5.3.2	Probes	7
5.3.3	Checking of the ultrasonic test equipment	8
5.3.4	Coupling medium	8
5.3.5	Time base range and sensitivity setting of the ultrasonic test equipment	8
5.3.6	Detection sensitivity	9
5.4	Preparation of casting surfaces for testing	9
5.5	Test procedure	9
5.5.1	General	9
5.5.2	Sensitivity setting	9
5.5.3	Consideration of various types of indications	10
5.5.4	Evaluation and recording of indications	10
5.5.5	Assessment of discontinuities to be recorded	10
5.5.6	Characterization and sizing of discontinuities	10
5.6	Test report	11
Annex A (informative) Significant technical changes between this document and the previous edition		21
Bibliography		23