

# DIN EN 12680-3:2026-03 (E)

## Founding - Ultrasonic testing - Part 3: Spheroidal graphite cast iron castings

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Requirements .....</b>	<b>5</b>
4.1	Order information .....	5
4.2	Extent of testing .....	5
4.3	Wall section zones .....	5
4.4	Maximum acceptable size of discontinuities .....	6
4.5	Qualification of personnel .....	6
4.6	Severity levels .....	6
<b>5</b>	<b>Testing .....</b>	<b>6</b>
5.1	Principles .....	6
5.2	Material .....	6
5.3	Equipment and coupling medium .....	6
5.3.1	Ultrasonic instrument .....	6
5.3.2	Probes .....	7
5.3.3	Checking of the ultrasonic test equipment .....	8
5.3.4	Coupling medium .....	8
5.3.5	Time base range and sensitivity setting of the ultrasonic test equipment .....	8
5.3.6	Detection sensitivity .....	9
5.4	Preparation of casting surfaces for testing .....	9
5.5	Test procedure .....	9
5.5.1	General .....	9
5.5.2	Sensitivity setting .....	9
5.5.3	Consideration of various types of indications .....	10
5.5.4	Evaluation and recording of indications .....	10
5.5.5	Assessment of discontinuities to be recorded .....	10
5.5.6	Characterization and sizing of discontinuities .....	10
5.6	Test report .....	11
Annex A (informative) Significant technical changes between this document and the previous edition .....		21
Bibliography .....		23